

Reptistar T8


F18W/Reptistar UV-B 5% Retail

0000732



Range Features

- Promotes vitamin D3 production which aids good health, growth and the general well-being of reptiles in terrariums through a high content of UVB (up to 5%) and UVA (up to 30%)
- This full spectrum (6500 K) lamp improves the natural appearance of reptiles
- Shows reptiles in their true colours
- Applications
- For the artificial lighting of reptiles in terrariums
- Directions for use
- This lamp emits UV-radiation. Avoid exposure to skin and eyes



PRODUCT OVERVIEW

Lamp finish	Coated
Lamp shape	Tubular
Colour temperature (K)	6500
Dimmable	Yes
EAN code	5410288007328
Cap/Base	G13
Type	ReptiStar
Watt (Nominal) (W)	18
Ordering number	0000732
Luminous flux (Rated) (lm)	450
Technology	Fluorescent
Voltage (V)	57

DATA TABLE

General data

Average life (Nominal) (h)	10000
Control gear required	Yes
Lamp finish	Coated
Lamp shape	Tubular
Dimmable	Yes
EAN code	5410288007328
Fixture rating	Open
General application	Retail; Hospitality; Logistics and Industry; Museums; Education; Office; Residential & Consumer
IEC Reference	IEC 60081
IEC Reference 2	IEC 61195

Reptistar T8

F18W/Reptistar UV-B 5% Retail

0000732

Intended purpose	Special lighting
Cap/Base	G13
Lamp mercury content (mg)	10
Type	ReptiStar
Ordering number	0000732

Range features

Promotes vitamin D3 production which aids good health, growth and the general well-being of reptiles in terrariums through a high content of UVB (up to 5%) and UVA (up to 30%)
 This full spectrum (6500 K) lamp improves the natural appearance of reptiles
 Shows reptiles in their true colours
 Applications
 For the artificial lighting of reptiles in terrariums
 Directions for use
 This lamp emits UV-radiation. Avoid exposure to skin and eyes

Product name	F18W/Reptistar UV-B 5% Retail
Special purpose lamp	Yes
Technology	Fluorescent
Transformer required	No
Sales pack quantity	10
E-number SE	8356665

Optical data

Colour temperature (K)	6500
Luminous flux (Nominal) (lm)	450
Luminous flux (Rated) (lm)	450

Electrical data

Current (A)	0.37
Watt (Nominal) (W)	18
Watt (Rated) (W)	18
Voltage (V)	57

Physical data

Max. Lamp Diameter (mm) - D	26
Lamp Length (mm) - C/L	604
Length base to base (mm) - A	589.8
Length base to pin Min-Max - B	594.5-596.9
Single packaging type	Box/Sleeve
Weight (kg)	0.08
Outer package dimensions (L x W x H) (cm)	70.10 x 6.50 x 14.70
Single package dimensions (L x W x H) (cm)	67.10 x 2.70 x 2.70

Reptistar T8

F18W/Reptistar UV-B 5% Retail

0000732

TECHNICAL DRAWINGS

