

## T8 Luxline® Plus

F58W/830

0001531



### Range Features

- 



### PRODUCT OVERVIEW

Lamp finish	Coated
Lamp shape	Linear
Colour temperature (K)	3000
CRI (Ra)	85
Dimmable	Yes
EAN code	5410288015316
Energy class	A
Cap/Base	G13
Type	T8 Luxline Plus
Watt (Nominal) (W)	58
Light colour	830 Warm White
Ordering number	0001531
Efficacy (Rated) (lm/w)	90
Luminous flux (Rated) (lm)	5200
Technology	Fluorescent
Voltage (V)	110

### DATA TABLE

#### Optical data

Ambient temperature for maximum luminous flux (°C)	25
Colour temperature (K)	3000
CRI (Ra)	85
Light colour	830 Warm White
Luminous flux (Nominal) (lm)	5200
Rated lumen maint. factor at 12000 h 50Hz	0.9
Rated lumen maint. factor at 16000 h 50Hz	0.89

## T8 Luxline® Plus

F58W/830

0001531

Rated lumen maint. factor at 20000 h 50Hz	0.87
Rated lumen maint. factor at 2000 h 50Hz	0.96
Rated lumen maint. factor at 4000 h 50Hz	0.94
Rated lumen maint. factor at 6000 h 50Hz	0.92
Rated lumen maint. factor at 8000 h 50Hz	0.91
Luminous flux (Rated) (lm)	5200

### General data

Average life (Nominal) (h)	20000
Control gear required	Yes
Lamp finish	Coated
Lamp shape	Linear
Dimmable	Yes
EAN code	5410288015316
Energy class	A
Fixture rating	Open
General application	Retail; Hospitality; Logistics and Industry; Museums; Education; Office; Residential & Consumer;
IEC Reference	IEC 60081
IEC Reference 2	IEC 61195
Intended purpose	General lighting
Cap/Base	G13
Lamp mercury content (mg)	2.8
Type	T8 Luxline Plus
Ordering number	0001531
Product name	F58W/830
Rated survival factor at 12000 h 50Hz	0.92
Rated survival factor at 16000 h 50Hz	0.8
Rated survival factor at 20000 h 50Hz	0.5
Rated survival factor at 2000 h 50Hz	0.99
Rated survival factor at 4000 h 50Hz	0.98
Rated survival factor at 6000 h 50Hz	0.96
Rated survival factor at 8000 h 50Hz	0.94
Special purpose lamp	No
Technology	Fluorescent
Transformer required	No
Sales pack quantity	25
E-number SE	8356612
E-number FI	4940778

## T8 Luxline® Plus

F58W/830

**0001531**


### Electrical data

<b>Current (A)</b>	0.67
<b>Ignition voltage (V)</b>	0
<b>kWh per 1000 hours burning time</b>	68
<b>Watt (Nominal) (W)</b>	58
<b>Efficacy (Rated) (lm/w)</b>	90
<b>Rated lamp efficacy (lm/W) 100H 50Hz at optimum temp.</b>	90
<b>Watt (Rated) (W)</b>	50
<b>Watt (Rated) - High frequency (W)</b>	50
<b>Voltage (V)</b>	110

### Physical data

<b>Diameter (mm)</b>	26
<b>Max. Lamp Diameter (mm) - D</b>	26
<b>Lamp Length (mm) - C/L</b>	1514.2
<b>Length base to base (mm) - A</b>	1500
<b>Length base to pin Min-Max - B</b>	1504.7-1507.1
<b>Single packaging type</b>	Box/Sleeve
<b>Weight (kg)</b>	0.20
<b>Outer package dimensions (L x W x H) (cm)</b>	154.50 x 15.50 x 15.00
<b>Single package dimensions (L x W x H) (cm)</b>	151.10 x 2.90 x 2.80

## TECHNICAL DRAWINGS



T8 Luxline® Plus

F58W/830

0001531

