# SYLVANIA

## T8 Coloured *F36W/T8/B* 0002567



#### **Range Features**

- High quality fluorescent tubes
- Long life
- Available in five colours: Blue, Green, Red, Pink and Yellow
- Applications
- To create special lighting effects in shop windows, bars, fairground attractions, dance halls and discotheques



#### **PRODUCT OVERVIEW**

Lamp finish	Coated
Lamp shape	Tubular
Dimmable	Yes
EAN code	5410288025674
Cap/Base	G13
Туре	T8 Coloured
Watt (Nominal) (W)	36
Ordering number	0002567
Luminous flux (Rated) (lm)	700
Technology	Fluorescent
Voltage (V)	103

#### **DATA TABLE**

General data	
Average life (Nominal) (h)	8000
Control gear required	Yes
Lamp finish	Coated
Lamp shape	Tubular
Dimmable	Yes
EAN code	5410288025674
Fixture rating	Open
General application	Retail; Hospitality; Logistics and Industry; Museums; Education; Office; Residential & Consumer



## T8 Coloured F36W/T8/B 0002567

IEC Reference	IEC 60081
IEC Reference 2	IEC 61195
Intended purpose	Special lighting
	G13
Cap/Base	
Type	T8 Coloured
Ordering number	0002567
Range features	High quality fluorescent tubes Long life Available in five colours: Blue, Green, Red, Pink and Yellow Applications To create special lighting effects in shop windows, bars, fairground attractions, dance halls and discotheques
Product name	F36W/T8/B
Special purpose lamp	Yes
Technology	Fluorescent
Transformer required	No
Sales pack quantity	25
E-number SE	8356736
	4942938
Electrical data	
Electrical data Current (A)	0.43
Current (A)	0.43
Current (A) Watt (Nominal) (W)	0.43 36
Current (A) Watt (Nominal) (W) Watt (Rated) (W)	0.43 36 36
Current (A) Watt (Nominal) (W) Watt (Rated) (W) Voltage (V)	0.43 36 36
Current (A) Watt (Nominal) (W) Watt (Rated) (W) Voltage (V) Physical data Max. Lamp Diameter (mm) - D	0.43 36 36 103
Current (A) Watt (Nominal) (W) Watt (Rated) (W) Voltage (V) Physical data	0.43 36 36 103 26
Current (A) Watt (Nominal) (W) Watt (Rated) (W) Voltage (V) Physical data Max. Lamp Diameter (mm) - D Lamp Length (mm) - C/L	0.43 36 36 103 26 1213.6
Current (A) Watt (Nominal) (W) Watt (Rated) (W) Voltage (V) Physical data Max. Lamp Diameter (mm) - D Lamp Length (mm) - C/L Length base to base (mm) - A	0.43 36 36 103 26 1213.6 1199.4
Current (A) Watt (Nominal) (W) Watt (Rated) (W) Voltage (V) Physical data Max. Lamp Diameter (mm) - D Lamp Length (mm) - C/L Length base to base (mm) - A Length base to pin Min-Max - B	0.43 36 36 103 26 1213.6 1199.4 1204.1-1206.5
Current (A) Watt (Nominal) (W) Watt (Rated) (W) Voltage (V) Physical data Max. Lamp Diameter (mm) - D Lamp Length (mm) - C/L Length base to base (mm) - A Length base to pin Min-Max - B Single packaging type Weight (kg)	0.43 36 36 103 26 1213.6 1199.4 1204.1-1206.5 Box/Sleeve
Current (A) Watt (Nominal) (W) Watt (Rated) (W) Voltage (V) Physical data Max. Lamp Diameter (mm) - D Lamp Length (mm) - C/L Length base to base (mm) - A Length base to pin Min-Max - B Single packaging type	0.43 36 36 103 26 1213.6 1199.4 1204.1-1206.5 Box/Sleeve
Current (A) Watt (Nominal) (W) Watt (Rated) (W) Voltage (V) Physical data Max. Lamp Diameter (mm) - D Lamp Length (mm) - C/L Length base to base (mm) - A Length base to pin Min-Max - B Single packaging type Weight (kg)	0.43 36 36 103 26 1213.6 1199.4 1204.1-1206.5 Box/Sleeve

### **TECHNICAL DRAWINGS**



### T8 Coloured F36W/T8/B 0002567

