

SHP-S / SHP-TS Twinarc

SA SHP-TS 50W TWINARC E27 SLV

0020712



Range Features

- Range of high pressure sodium lamps with double arc tube construction
- Dual arc tube design guarantees immediate re-strike after a power interruption
- Doubled lamp life and reduced occurrence of early failures
- Exceptional reliability, offering 6 years of maintenance-free service and superior lumen maintenance, exceeding 95% over life
- Ideal for applications which are difficult to access, or where maintenance is expensive
- Perfect for tunnels, airports, military installations, harbours and industrial sites



PRODUCT OVERVIEW

Lamp finish	clear
Lamp shape	tubular
Colour temperature (K)	2050
CRI (Ra)	20
Dimmable	Yes
EAN code	5410288207124
Energy class	A
Cap/Base	E27
Type	SHP-TS
Watt (Nominal) (W)	50
Light colour	0
Ordering number	0020712
Efficacy (Rated) (lm/w)	79
Average life (Rated) (h)	40000
Luminous flux (Rated) (lm)	4000
Technology	HID
Voltage (V)	85

DATA TABLE

Optical data

Ambient temperature for maximum luminous flux (°C)	25
Colour temperature (K)	2050
CRI (Ra)	20
Light colour	0
Luminous flux (Nominal) (lm)	4000

SHP-S / SHP-TS Twinarc

SA SHP-TS 50W TWINARC E27 SLV
0020712

Rated lumen maint. factor at 12000 h	0.91
Rated lumen maint. factor at 12000 h 50Hz	0.91
Rated lumen maint. factor at 16000 h	0.9
Rated lumen maint. factor at 16000 h 50Hz	0.9
Rated lumen maint. factor at 20000 h	0.89
Rated lumen maint. factor at 20000 h 50Hz	0.89
Rated lumen maint. factor at 2000 h	0.98
Rated lumen maint. factor at 2000 h 50Hz	0.98
Rated lumen maint. factor at 4000 h	0.96
Rated lumen maint. factor at 4000 h 50Hz	0.96
Rated lumen maint. factor at 6000 h	0.94
Rated lumen maint. factor at 6000 h 50Hz	0.94
Rated lumen maint. factor at 8000 h	0.93
Rated lumen maint. factor at 8000 h 50Hz	0.93
Luminous flux (Rated) (lm)	4000

General data

Average life (Nominal) (h)	40000
Control gear required	yes
Lamp finish	clear
Lamp shape	tubular
Dimmable	Yes
EAN code	5410288207124
Energy class	A
Fixture rating	open
General application	Logistics and Industry; Outdoor
IEC Reference	IEC 60662
IEC Reference 2	IEC 62035
Intended purpose	General lighting
Cap/Base	E27
Lamp mercury content (mg)	14.4
Type	SHP-TS
Life T90	21000

SHP-S / SHP-TS Twinarc

SA SHP-TS 50W TWINARC E27 SLV

0020712

Notes	<p>Sylvania SHP lamps can be dimmed with negligible impact on performance creating the potential for flexible light levels and reduced energy consumption.</p> <p>Dimming is supported on electronic square wave ballasts and magnetic systems that can maintain the open circuit voltage. Square wave operation is recommended.</p> <p>Dimming causes a reduction of light and some colour change. We advise to start the lamps at full power and to hold this for 15 minutes before reducing the power. To avoid extinguishing the power should be adjusted gradually taking a few minutes to reach the final dimming condition.</p> <p>Square wave dimming down to 50% of the rated power will have negligible impact on performance, dimming down to 35% of the rated power can affect lumen maintenance and colour appearance.</p> <p>Dimming by means of voltage on magnetic systems is not advised as this increases the chance of lamp extinguishing. Dimming by phase-cutting on magnetic systems is not allowed. Instant dimming on magnetic systems by adding an impedance is suggested down to 50% of the rated power but the average life can be reduced.</p>
Ordering number	0020712
Range features	<p>Range of high pressure sodium lamps with double arc tube construction</p> <p>Dual arc tube design guarantees immediate re-strike after a power interruption</p> <p>Doubled lamp life and reduced occurrence of early failures</p> <p>Exceptional reliability, offering 6 years of maintenance-free service and superior lumen maintenance, exceeding 95% over life</p> <p>Ideal for applications which are difficult to access, or where maintenance is expensive</p> <p>Perfect for tunnels, airports, military installations, harbours and industrial sites</p>
Product name	SA SHP-TS 50W TWINARC E27 SLV
Average life (Rated) (h)	40000
Rated survival factor at 12000 h	0.98
Rated survival factor at 12000 h 50Hz	0.98
Rated survival factor at 16000 h	0.95
Rated survival factor at 16000 h 50Hz	0.95
Rated survival factor at 20000 h	0.91
Rated survival factor at 20000 h 50Hz	0.91
Rated survival factor at 2000 h	1
Rated survival factor at 2000 h 50Hz	1
Rated survival factor at 4000 h	1
Rated survival factor at 4000 h 50Hz	1
Rated survival factor at 6000 h	1
Rated survival factor at 6000 h 50Hz	1
Rated survival factor at 8000 h	0.99
Rated survival factor at 8000 h 50Hz	0.99

SHP-S / SHP-TS Twinarc SA SHP-TS 50W TWINARC E27 SLV 0020712

Special purpose lamp	No
Technology	HID
Transformer required	no
Sales pack quantity	40
E-number SE	8358005
E-number FI	4845525

Electrical data


Current (A)	0.76
kWh per 1000 hours burning time	55
Watt (Nominal) (W)	50
Efficacy (Rated) (lm/w)	79
Watt (Rated) (W)	50
Voltage (V)	85

Physical data

Max. Lamp Diameter (mm) - D	39
Lamp Length (mm) - C/L	156
Single packaging type	Box/Sleeve
Weight (kg)	0.05
Outer package dimensions (L x W x H) (cm)	42.00 x 28.00 x 21.00
Single package dimensions (L x W x H) (cm)	20.00 x 4.20 x 4.20


TECHNICAL DRAWINGS

SHP-TS TWINARC




SHP-TS	35W	50W	70W	100W	150W	250W	400W
L	156	156	156	211	211	260	292
D	39	39	39	48	48	48	48


Ballast Curve (SHP-TS) TWINARC 35-50W



E27



Lumen Maintenance curve
SHP-TS TWINARC 35-50W



SHP-S / SHP-TS Twinarc
SA SHP-TS 50W TWINARC E27 SLV
0020712

