

Blacklight BL368 Compact MiniLynx

MiniLynx 20W BL368

0025706



Range Features

- Features
- These BL368 tubes emit an upgraded highly concentrated radiation with peak around 368nm. Flying insect - eye sensitivity is generally at or near this frequency
- 100% improvement in effectiveness (at 368nm)
- Depreciation of UV-A output over time is significantly reduced (80% at 5000hrs of original 100 hour output)
- Performs longer and better throughout the insect season
-
- Directions for use
- Maximum exposure limits are set by EN60335 2-59:1997 at an effective 1,0 milliWatt per metre squared (1,0 mW/m²) measured at a distance of 1 metre - originally based on the recommendations of the National Radiological Protection Board in the UK. The irradiance value for a single BL BL368-lamp measured without reflector and/or fixture, in free air at 25 celsius, is varying between 0,2 and 0,4 mW/m² depending on the wattage



PRODUCT OVERVIEW

Colour temperature (K)	UV-A lamp
EAN code	5410288257068
Cap/Base	E27
Type	BL368
Watt (Nominal) (W)	20
Ordering number	0025706
Technology	Fluorescent
Voltage (V)	230

DATA TABLE

Optical data

Colour temperature (K)	UV-A lamp
------------------------	-----------

General data

EAN code	5410288257068
General application	Retail; Hospitality; Logistics and Industry; Museums; Education; Office; Residential & Consumer
Intended purpose	Special lighting
Cap/Base	E27
Type	BL368
Ordering number	0025706

Blacklight BL368 Compact MiniLynx

MiniLynx 20W BL368

0025706

Range features	<p>Features These BL368 tubes emit an upgraded highly concentrated radiation with peak around 368nm. Flying insect - eye sensitivity is generally at or near this frequency 100% improvement in effectiveness (at 368nm) Depreciation of UV-A output over time is significantly reduced (80% at 5000hrs of original 100 hour output) Performs longer and better throughout the insect season</p> <p>Directions for use Maximum exposure limits are set by EN60335 2-59:1997 at an effective 1,0 milliWatt per metre squared (1,0 mW/m) measured at a distance of 1 metre - originally based on the recommendations of the National Radiological Protection Board in the UK. The irradiance value for a single BL BL368-lamp measured without reflector and/or fixture, in free air at 25 celsius, is varying between 0,2 and 0,4 mW/m depending on the wattage</p>
Product name	MiniLynx 20W BL368
Special purpose lamp	Yes
Technology	Fluorescent
Sales pack quantity	10
E-number FI	4940706
Electrical data	
Watt (Nominal) (W)	20
Voltage (V)	230
Physical data	
Single packaging type	Box/Sleeve
Weight (kg)	0.09

TECHNICAL DRAWINGS

E27

