

PRODUCT DATASHEET

HALOSPOT 111 PRO 60 W 12 V 40° G53

PARATHOM® Retrofit CLASSIC B | LED lamps, classic mini-candle shape



Areas of application

- General illumination
- Entrance lighting
- Shops
- Restaurants, hotels and similar prestigious applications
- Offices, public buildings

Product benefits

- Brilliant accent lighting
- Significantly lower CO₂ emissions compared to standard version
- Cap for reduced glare and ease of handling
- New high-tech reflector for optimum illumination and reduced scatter
- Approved for use in open luminaires (to IEC 60598-1)
- UV filter
- Drastically reduced thermal load in luminaire thanks to aluminum-coated reflector
- Contains no mercury

Product features

- Average life: 4,000 h
- 100 % dimmable
- Color rendering index R_a: 100
- Diameter: 111 mm
- IRC technology

TECHNICAL DATA

Electrical data

Nominal wattage	60 W
Nominal voltage	12.00 V
Claimed equiv. conventional lamp power	90 W
Nominal current	5.41 A
Power factor λ	1,00

Photometrical data

Luminous intensity	2800 cd
Luminous flux	870 lm
Nominal useful luminous flux 90°	870 lm
Luminous efficacy	14 lm/W
Lumen main.fact.at end of nom.life time	0.75
Light color (designation)	Warm White
Color temperature	3000 K
Color rendering index Ra	100
Light color	1030
Rated peak intensity	2800 cd
UV protection	Yes

Light technical data

Beam angle	40 °
Warm-up time (60 %)	0.00 s
Starting time	0.0 s
Rated beam angle (half peak value)	40.00 °

Dimensions & weight

Overall length	56.00 mm
Length	67.00 mm
Diameter	111,0 mm
Maximum diameter	111 mm
Product weight	48.33 g

Lifespan

Nominal lamp life time	4000 h
Number of switching cycles	100000

Additional product data

Base (standard designation)	G53
Mercury content	0.0 mg
Mercury-free	Yes
Design / version	Reflector
Product remark	If connectors are used, an additional holder is required at the rim of the reflector / May produce noise in combination with some dimmers. Recommended solution: use OSRAM HTi DALI 150/230-240 DIM with OSRAM DALI MCU

Capabilities

Dimmable	Yes
Burning position	Any



Certificates & standards

Energy efficiency class	B
Energy consumption	65.00 kWh/1000h

Country-specific categorizations

ILCOS	HMGS//UBIB-60-12-G53-111/40
Order reference	48837 ECO WFL

DOWNLOAD DATA

DOWNLOAD DATA	
	CAD data 3-dim 320835_HALOSPOT 111
	CAD data 3-dim 320836_HALOSPOT 111

LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4008321909251	Folding box 1	112 mm x 86 mm x 87 mm	84.00 g	0.84 dm ³
4008321909268	Shipping box 6	275 mm x 130 mm x 185 mm	633.00 g	6.61 dm ³

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.