

PRODUCT DATASHEET

HALOPIN PRO 33 W 240 V G9

PARATHOM® CLASSIC A | LED lamps, classic bulb shape



Areas of application

- General illumination
- Workplace lighting
- Lighting for reading
- Dining table lighting
- Mirror lighting
- Accent lighting
- Mood lighting

Product benefits

- Brilliant accent lighting
- Incredibly small dimensions for revolutionary new luminaire designs
- Robust filament design thanks to innovative, unique bulb pinch technology
- Approved for use in open luminaires (to IEC 60598-1)
- UV filter
- Complies with IEC 60432-2 thanks to integrated fuse function
- Lower thermal output (compared with the standard reference product)
- The lamp shuts down reliably
- Contains no mercury

Product features

- Average life: 2,000 h
- Dimmable
- Color rendering index R_a : 100

TECHNICAL DATA

Electrical data

| | |
|--|-------|
| Nominal wattage | 33 W |
| Nominal voltage | 240 V |
| Claimed equiv. conventional lamp power | 40 W |
| Power factor λ | 1,00 |

Photometrical data

| | |
|---|------------|
| Luminous flux | 460 lm |
| Luminous efficacy | 13 lm/W |
| Lumen main.fact.at end of nom.life time | 0.80 |
| Light color (designation) | Warm White |
| Color temperature | 2700 K |
| Color rendering index Ra | 100 |
| Light color | 1027 |

Light technical data

| | |
|---------------------|--------|
| Warm-up time (60 %) | 0.00 s |
| Starting time | 0.0 s |

Dimensions & weight

| | |
|---------------------------|----------|
| Overall length | 43.00 mm |
| Length | 43.00 mm |
| Light center length (LCL) | 22,0 mm |
| Diameter | 14.00 mm |
| Maximum diameter | 14 mm |
| Product weight | 2.9 g |

Lifespan

| | |
|----------------------------|--------|
| Nominal lamp life time | 2000 h |
| Number of switching cycles | 50000 |

Additional product data

| | |
|-----------------------------|--------|
| Base (standard designation) | G9 |
| Mercury content | 0.0 mg |
| Mercury-free | Yes |
| Design / version | Tube |

Capabilities

| | |
|----------|-----|
| Dimmable | Yes |
|----------|-----|

| | |
|------------------|-----|
| Burning position | Any |
|------------------|-----|


Certificates & standards

| | |
|-------------------------|-----------------|
| Energy efficiency class | D |
| Energy consumption | 33.00 kWh/1000h |

Country-specific categorizations

| | |
|-----------------|-------------------------|
| ILCOS | HSGST/C/UB-33-240-G9-22 |
| Order reference | 66733 ECO |

DOWNLOAD DATA

| DOWNLOAD DATA | |
|--|---|
|  | Certificates EAEC N RU D-DE.MYu62.B.01507 20 09.04.2020-08.04.2025 |

LOGISTICAL DATA

| Product code | Packaging unit (Pieces/Unit) | Dimensions (length x width x height) | Gross weight | Volume |
|---------------|------------------------------|--------------------------------------|--------------|----------------------|
| 4008321226341 | Folding box 1 | 70 mm x 23 mm x 25 mm | 6.50 g | 0.04 dm ³ |
| 4058075666979 | Bundle 2 | 25 mm x 46 mm x 70 mm | 14.00 g | 0.08 dm ³ |
| 4008321226358 | Shipping box 20 | 144 mm x 70 mm x 106 mm | 128.00 g | 1.07 dm ³ |
| 4058075666986 | Shipping box 20 | 144 mm x 55 mm x 118 mm | 166.00 g | 0.93 dm ³ |

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.