MASTER LEDtube EM/ Mains

MAS LEDtube 1500mm SO 20W 865 T8

The Philips MASTER LEDtube integrates a LED light source into a traditional fluorescent form factor. Its unique design creates a perfectly uniform visual appearance which cannot be distinguished from traditional fluorescent. For those that are looking for value for money within limited budget and re-lamping efforts for better light effect and lifetime.

Product data

General Information

PHILIPS

General mormation	
Cap-Base	G13 [Medium Bi-Pin Fluorescent]
Main Application	Industrial
Nominal Lifetime (Nom)	50000 h
Switching Cycle	200000×
B50L70	50000

• Light Technical

Color Code	865 [CCT of 6500K]
Beam Angle (Nom)	160 °
Luminous Flux	2000 lm
(Rated) (Nom)	
Rated Beam Angle	160 °
Correlated Color	6500 K
Temperature (Nom)	
Color Consistency	<lt></lt> 6
Color Rendering	83
Index (Nom)	
Llmf At End Of	70 %
Nominal Lifetime	
(Nom)	
()	

• Operating and Electrical

Input Frequency	50/60 Hz
Power (Rated)	20 W
(Nom)	
Starting Time (Max)	0.5 s
Warm Up Time To	instant full light
60% Light (Nom)	
Power Factor (Min)	0.9
Voltage (Nom)	220-240 V

Temperature	
T Ambient (N	

T-Ambient (Max)	45 °C
T-Ambient (Min)	-20 °C
T-Storage (Max)	65 °C
T-Storage (Min)	-40 °C
T-Case Maximum	50 °C
(Max)	

Controls and Dimming

Dimmable	No
----------	----

• Mechanical and Housing

Product Length	1500 mm
----------------	---------

• Approval and Application

Energy Saving Product	Yes
Suitable For Accent	No
Energy Efficiency Label (EEL)	A+
Approval Marks	CE marking RoHS compliance KEMA Keur certificate
Energy Consumption kWh/1000 h	20 kWh

• Product Data

Full product code Order product name

EAN/UPC - Product Order code

871829173453600 MAS LEDtube 1500mm SO 20W 865 Т8 8718291734536 929000287702



MASTER LEDtube EM/Mains


Numerator - Quan- 1 tity Per Pack Numerator - Packs 10 per outer box Material Nr. (12NC) Net Weight (Piece)

) 929000287702 0.450 kg

Warnings and Safety

• _

Dimensional drawing



MASTER LEDtube HF, VLE, VALUE HF



LEDtube VLE 1600mm 20W/865 T8 C

Product	D1	D2	A1	A2	A3
MAS LEDtube 1500mm SO 20W 865 T8	25.68 mm	28 mm	1500.0 mm	1507.1 mm	1514.2 mm



 $\ensuremath{\mathbb{C}}$ 2016 Philips Lighting Holding B.V. All rights reserved.

Specifications are subject to change without notice. Trademarks are the property of Koninklijke Philips N.V. (Royal Philips) or their respective owners.

www.philips.com/lighting