
SPC.T CL 25 W 230 V E14

SPECIAL T | Incandescent lamps, tubular shape



Product datasheet

Technical data

Electrical data

Rated wattage	25.00 W
Nominal wattage	25.00 W
Nominal voltage	230 V
Power factor λ	1.00


Photometrical data

Nominal luminous flux	160 lm
Color temperature	2700 K
Color rendering index Ra	100
Luminous flux	160 lm
Color rendering index Ra	100

Light technical data

Starting time	0.0 s
---------------	-------

Dimensions & weight



Diameter	26.0 mm
Overall length	57.0 mm
Outer bulb	T26
Length	57.0 mm

Lifespan

Nominal lamp life time	1000 h
Rated lamp life time	1000 h

Additional product data

Product datasheet

Base (standard designation)	E14
Lamp mercury content	0.0 mg
Mercury-free	Yes

Capabilities

Dimmable	Yes
----------	-----

Certificates & standards

Energy efficiency class	E
Energy consumption	25 kWh/1000h

Country specific categorizations

ILCOS	IBT/C-25-230-E14-26
-------	---------------------

Logistical Data

Product code	Product description	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Volume	Gross weight
4050300309637	SPC.T CL 25 W 230 V E14	Shipping carton box 100	285 mm x 140 mm x 150 mm	5.99 dm ³	1301.00 g
4050300774664	SPC.T CL 25 W 230 V E14	Shipping carton box 20	286 mm x 141 mm x 149 mm	6.01 dm ³	458.00 g
7039210610832	SPC.T CL 25 W 230 V E14	Shipping carton box 100	310 mm x 145 mm x 110 mm	4.94 dm ³	1343.00 g

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.