

# PRODUCT DATASHEET

## PLANON Frameless CCT 1200x300 60 W

PLANON Frameless RGB+CCT | Frameless panel luminaires for wall and ceiling mounting for RGB and CCT color adjustment via remote control

---

### AREAS OF APPLICATION

- Indoor applications
- Decorative domestic lighting
- Wall and ceiling surface mounting



---

### PRODUCT BENEFITS

- Homogenous light distribution
- Easy and quick installation

---

### PRODUCT FEATURES

- Ceiling luminaire with advanced LED technology
- Available in square and rectangular form
- Color changing (RGB) and white adjustment (CCT) from 3000 K...5000 K via infrared remote control
- Dimmable from 10...100 % via infrared remote control
- Aluminum housing, frosted PMMA diffuser



**TECHNICAL DATA**

Electrical data

<b>Nominal wattage</b>	60.00 W
<b>Operating mode</b>	Mains voltage
<b>Nominal voltage</b>	220...240 V
<b>Mains frequency</b>	50/60 Hz

Photometrical data

<b>Color temperature</b>	3000 ... 5000 K
<b>Color rendering index Ra</b>	≥80
<b>Light color (designation)</b>	Warm White...Cool White
<b>Luminous flux</b>	3300 lm
<b>Luminous efficacy</b>	55 lm/W

Light technical data

<b>Beam angle</b>	120 °
-------------------	-------

Dimensions & weight



<b>Length</b>	1195 mm
<b>Width</b>	295.0 mm
<b>Height</b>	60.0 mm
<b>Product weight</b>	8500.00 g

Colors & materials

<b>Body material</b>	Aluminum
<b>Product color</b>	White
<b>Housing color</b>	White
<b>Cover material</b>	Polymethylmethacrylate (PMMA)
<b>Light emitting surface material</b>	PMMA

## Temperatures &amp; operating conditions

Ambient temperature range	-25...+35 °C
---------------------------	--------------

## Lifespan

Number of switching cycles	15000
Lifespan	25000 h

## Additional product data

Mounting type	Surface
Mounting location	Ceiling

## Capabilities

Dimmable	Yes
Type of connection	Screw terminal
LED module replaceable	Not replaceable

## Certificates &amp; standards

Protection class	I
Type of protection	IP20
Standards	CE/EAC/REACH/RoHS

## EQUIPMENT / ACCESSORIES

- Complete mounting and connecting accessories included
- Remote control and battery included
- Driver included

## LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4058075257290	Folding carton box 1	83 mm x 1223 mm x 325 mm	8916.00 g	32.99 dm <sup>3</sup>
4058075257306	Shipping carton box 2	1240 mm x 180 mm x 340 mm	18419.00 g	75.89 dm <sup>3</sup>

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

## DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.