

# PRODUCT DATASHEET

## SST CLAS B 40 GLOWdim 4.5 W/2700K E14

LED SUPERSTAR CLASSIC B GLOWdim | LED lamps with GLOWdim effect, classic candle shape



### AREAS OF APPLICATION

- Hospitality
- Historical buildings
- Residential interiors
- Marine lighting
- Outdoor use in outdoor luminaires only (minimum IP65)

### PRODUCT BENEFITS

- Provides an especially warm light when dimmed down
- Directly controllable via standard dimmer, no remote control required
- Can be easily combined with other GLOWdim products in one application
- Very long lifetime of up to 25,000 h
- Low energy consumption
- Easy relamping thanks to compact design

### PRODUCT FEATURES

- LED alternative to conventional lamps
- Dimming changes light color from warm white (2,700 K) to extra warm white (2,000 K)
- Good quality of light; color rendering index  $R_a \geq 80$
- Dimmable (with many common dimmers, see also [www.ledvance.com/dim](http://www.ledvance.com/dim))
- Mercury-free lamps



## TECHNICAL DATA


### Electrical data

Rated wattage	4.50 W
Nominal wattage	4.50 W
Nominal voltage	220...240 V
Max. lamp no. on circuit break. 10 A (B)	227
Max. lamp no. on circuit break. 16 A (B)	364
Operating frequency	50...60 Hz

### Photometrical data

Lumen main.fact.at end of nom.life time	0.70
Light color (designation)	Tunable Warm White
Color temperature	2700 K
Luminous flux	470 lm
Color rendering index Ra	≥80
Adjustable color temperature	2200...2700 K
Nominal luminous flux	470 lm
Rated color temperature	2700 K

### Dimensions & weight



Overall length	118.0 mm
----------------	----------

### Temperatures & operating conditions

Ambient temperature range	-20...+40 °C
Maximum temperature at tc test point	65 °C

### Lifespan

Nominal lamp life time	15000 h
Rated lamp life time	15000 h

<b>Number of switching cycles</b>	100000
-----------------------------------	--------

## Additional product data

<b>Base (standard designation)</b>	E14
<b>Mercury-free</b>	Yes
<b>Product remark</b>	All technical parameters apply to the entire lamp/Due to the complex production process for light-emitting diodes, the typical values shown for the technical LED parameters are purely statistical values that do not necessarily match the actual technical parameters of each individual product, which can vary from the typical value

## Capabilities

<b>Dimmable</b>	Yes
-----------------	-----

## Certificates &amp; standards

<b>Energy efficiency class</b>	A++
--------------------------------	-----

## Country-specific categorizations

<b>ILCOS</b>	DRBB/C-5-827-220-240-E14-35
<b>Order reference</b>	LEDSCLB40GD 4,5

## LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4058075435490	Folding carton box 1	36 mm x 49 mm x 155 mm	44.00 g	0.27 dm <sup>3</sup>
4058075435506	Shipping carton box 4	109 mm x 89 mm x 128 mm	216.00 g	1.24 dm <sup>3</sup>
4058075454866	Shipping carton box 32	236 mm x 196 mm x 285 mm	2070.00 g	13.18 dm <sup>3</sup>
4058075808140	Blister 1	42 mm x 140 mm x 120 mm	39.00 g	0.71 dm <sup>3</sup>
4058075809574	Shipping carton box 6	261 mm x 153 mm x 136 mm	368.00 g	5.43 dm <sup>3</sup>

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

## DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.