

PRODUCT DATASHEET

ENDURA STYLE LANTERN FLARE 60CM Post 7W

ENDURA STYLE FLARE | Stainless steel wall luminaires with indirect illumination



TECHNICAL DATA

Electrical data

Nominal wattage	7.00 W
Operating mode	Mains voltage
Nominal voltage	220...240 V
Power factor λ	> 0,5


Photometrical data

Color temperature	3000 K
Luminous flux	470 lm
Luminous efficacy	67 lm/W
Light color	Warm White
Standard deviation of color matching	< 6 sdcm
Color rendering index Ra	≥ 80

Light technical data

Beam angle	230.00 °
------------	----------

Dimensions & weight



Diameter	110.00 mm
Height	604.00 mm
Product weight	1100.00 g

Colors & materials

Body material	Aluminum
Product color	Dark gray
Housing color	Dark gray
Cover material	Polycarbonate (PC)

Temperatures & operating conditions

Ambient temperature range	-20...+40 °C
---------------------------	--------------

Lifespan

Number of switching cycles	12500
Lifespan L70/B50 at 25 °C	25000 h

Additional product data

Mounting type	Surface
Mounting location	Ground



Capabilities

Dimmable	No
Type of connection	Terminal, 3-Pole (L, N, PE)
LEDmod replaceable	Not replaceable

Certificates & standards

Protection class	I
Type of protection	IP44
Standards	CE / EAC / REACH / RoHS

DOWNLOAD DATA

DOWNLOAD DATA	
	User instruction ENDURA STYLE LANTERN FLARE
	Tender documents Tender Text 4058075478053

LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4058075478053	Folding box 1	122 mm x 122 mm x 624 mm	1130.00 g	9.29 dm ³
4058075478060	Shipping box 2	638 mm x 258 mm x 147 mm	2795.00 g	24.20 dm ³

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.



DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.

