

# PRODUCT DATASHEET ENDURA STYLE CRYSTAL Wall updown 9W

ENDURA STYLE CRYSTAL | Stainless steel wall luminaires and bollards with indirect illumination





# **TECHNICAL DATA**


# Electrical data

| Nominal wattage        | 9.00 W        |
|------------------------|---------------|
| Operating mode         | Mains voltage |
| Nominal voltage        | 220240 V      |
| Power factor $\lambda$ | > 0,5         |

# Photometrical data

| Color temperature                    | 3000 K     |  |
|--------------------------------------|------------|--|
| Luminous flux                        | 800 lm     |  |
| Luminous efficacy                    | 89 lm/W    |  |
| Light color                          | Warm White |  |
| Standard deviation of color matching | < 6 sdcm   |  |
| Color rendering index Ra             | ≥80        |  |

# Dimensions & weight



| Length         | 105.00 mm |
|----------------|-----------|
| Height         | 215.00 mm |
| Width          | 80.00 mm  |
| Product weight | 1100.00 g |

# Colors & materials

| Body material  | Steel                         |  |
|----------------|-------------------------------|--|
| Product color  | Steel                         |  |
| Housing color  | Steel                         |  |
| Cover material | Polymethylmethacrylate (PMMA) |  |

# Temperatures & operating conditions



| Ambient temperature range -20+40 °C |
|-------------------------------------|
|-------------------------------------|

## Lifespan

| Number of switching cycles | 12500   |
|----------------------------|---------|
| Lifespan L70/B50 at 25 °C  | 25000 h |

# Additional product data

| Mounting type     | Surface |
|-------------------|---------|
| Mounting location | Wall    |

# **Capabilities**

| Dimmable           | No                          |  |
|--------------------|-----------------------------|--|
| Type of connection | Terminal, 3-Pole (L, N, PE) |  |
| LEDmod replaceable | Not replaceable             |  |

### Certificates & standards

| Protection class   | 1                       |
|--------------------|-------------------------|
| Type of protection | IP44                    |
| Standards          | CE / EAC / REACH / RoHS |

## **DOWNLOAD DATA**

|     | DOWNLOAD DATA                              |
|-----|--|
| PDF | User instruction ENDURA STYLE CRYSTAL WALL |
|     | Tender documents Tender Text 4058075474130 |
| PDF | Packaging insert<br>Legal insert           |

## **LOGISTICAL DATA**

| Product code  | Packaging unit (Pieces/Unit) | Dimensions (length x width x height) | Gross weight | Volume               |
|---------------|------------------------------|--------------------------------------|--------------|----------------------|
| 4058075474130 | Folding box<br>1             | 117 mm x 107 mm x 239 mm             | 1191.00 g    | 2.99 dm <sup>3</sup> |
| 4058075474147 | Shipping box<br>6            | 335 mm x 250 mm x 255 mm             | 7645.00 g    | 21.36 dm³            |

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.



# DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.

