

# PRODUCT DATASHEET

## ENDURA STYLE CRYSTAL 40CM Post 4.5W

ENDURA STYLE CRYSTAL | Stainless steel wall luminaires and bollards with indirect illumination



## TECHNICAL DATA


### Electrical data

Nominal wattage	4.50 W
Operating mode	Mains voltage
Nominal voltage	220...240 V
Power factor $\lambda$	> 0,5

### Photometrical data

Color temperature	3000 K
Luminous flux	400 lm
Luminous efficacy	89 lm/W
Light color	Warm White
Standard deviation of color matching	< 6 sdc <sub>m</sub>
Color rendering index Ra	≥80

### Dimensions & weight



Length	80.00 mm
Height	400.00 mm
Width	80.00 mm
Product weight	1250.00 g

### Colors & materials

Body material	Steel
Product color	Steel
Housing color	Steel
Cover material	Polymethylmethacrylate (PMMA)



## Temperatures & operating conditions

Ambient temperature range	-20...+40 °C
---------------------------	--------------

## Lifespan

Number of switching cycles	12500
Lifespan L70/B50 at 25 °C	25000 h

## Additional product data

Mounting type	Surface
Mounting location	Ground




## Capabilities

Dimmable	No
Type of connection	Terminal, 3-Pole (L, N, PE)
LEDmod replaceable	Not replaceable

## Certificates & standards

Protection class	I
Type of protection	IP44
Standards	CE / EAC / REACH / RoHS

## DOWNLOAD DATA

DOWNLOAD DATA	
	User instruction ENDURA STYLE CRYSTAL
	Tender documents Tender Text 4058075474253
	Packaging insert Legal insert

## LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4058075474253	Folding box 1	107 mm x 107 mm x 424 mm	1363.00 g	4.85 dm <sup>3</sup>
4058075474260	Shipping box 6	335 mm x 230 mm x 440 mm	8781.00 g	33.90 dm <sup>3</sup>

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

---

## DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.

