

PRODUCT DATASHEET

ENDURA STYLE PLATE Wall 12W

ENDURA STYLE PLATE | Stainless steel wall luminaires with indirect illumination



TECHNICAL DATA

Electrical data

Nominal wattage	12.00 W
Operating mode	Mains voltage
Nominal voltage	220...240 V
Power factor λ	$\geq 0,5$


Photometrical data

Color temperature	3000 K
Luminous flux	600 lm
Luminous efficacy	50 lm/W
Light color	Warm White
Standard deviation of color matching	< 6 sdc _m
Color rendering index Ra	≥ 80

Light technical data

Beam angle	108 °
------------	-------

Dimensions & weight



Length	54.00 mm
Height	280.00 mm
Width	180.00 mm
Product weight	670.00 g

Colors & materials

Body material	Steel
Product color	Steel
Housing color	Steel

Cover material	Polycarbonate (PC)
----------------	--------------------

Temperatures & operating conditions

Ambient temperature range	-20...+40 °C
---------------------------	--------------

Lifespan

Number of switching cycles	12500
Lifespan L70/B50 at 25 °C	25000 h

Additional product data

Mounting type	Surface
Mounting location	Wall

Capabilities

Dimmable	No
Type of connection	Terminal, 2-Pole (L, N)
LEDmod replaceable	Not replaceable

Certificates & standards

Protection class	II
Type of protection	IP44
Standards	CE / EAC / REACH / RoHS

DOWNLOAD DATA

DOWNLOAD DATA	
	User instruction ENDURA STYLE PLATE WALL
	Tender documents Tender Text 4058075477858

LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4058075477858	Folding box 1	60 mm x 185 mm x 290 mm	741.00 g	3.22 dm ³
4058075477865	Shipping box 4	310 mm x 260 mm x 205 mm	3282.00 g	16.52 dm ³

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products.

When placing an order, for the quantity please enter single or multiples of a shipping unit.

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.