

# PRODUCT DATASHEET ENDURA STYLE PLATE Wall Sensor 12,5W

ENDURA STYLE PLATE | Stainless steel wall luminaires with indirect illumination





## **TECHNICAL DATA**

## Electrical data

| Nominal wattage        | 12.50 W       |
|------------------------|---------------|
| Operating mode         | Mains voltage |
| Nominal voltage        | 220240 V      |
| Power factor $\lambda$ | ≥0,5          |

## Luminaire sensor data

| Type of sensor                         | Light / Motion         |
|--|------------------------|
| Sensor technology                      | Passive infrared (PIR) |
| Sensor detection angle                 | 100 °                  |
| Sensor controlled switching time       | 10 s4 min              |
| Detection range of motion sensor       | 58 m                   |
| Detection threshold of daylight sensor | 102000 lx              |


## Photometrical data

| Color temperature                    | 3000 K     |
|--------------------------------------|------------|
| Luminous flux                        | 630 lm     |
| Luminous efficacy                    | 48 lm/W    |
| Light color                          | Warm White |
| Standard deviation of color matching | < 6 sdcm   |
| Color rendering index Ra             | ≥80        |

# Light technical data

| Beam angle | 108 ° |
|------------|-------|
| -          |       |

# Dimensions & weight





| Height         | 283.00 mm |
|----------------|-----------|
| Width          | 180.00 mm |
| Product weight | 680.00 g  |

#### Colors & materials

| Body material  | Steel              |
|----------------|--------------------|
| Product color  | Steel              |
| Housing color  | Steel              |
| Cover material | Polycarbonate (PC) |

## Temperatures & operating conditions

| Ambient temperature range | -20+40 °C |
|---------------------------|-----------|
|---------------------------|-----------|

#### Lifespan

| Number of switching cycles | 12500   |
|----------------------------|---------|
| Lifespan L70/B50 at 25 °C  | 25000 h |

## Additional product data

| Mounting type     | Surface |
|-------------------|---------|
| Mounting location | Wall    |

# **Capabilities**

| Dimmable           | No                      |
|--------------------|-------------------------|
| Type of connection | Terminal, 2-Pole (L, N) |
| LEDmod replaceable | Not replaceable         |

## Certificates & standards

| Protection class   | Ш                       |
|--------------------|-------------------------|
| Type of protection | IP44                    |
| Standards          | CE / EAC / REACH / RoHS |

#### **DOWNLOAD DATA**

|     | DOWNLOAD DATA                              |
|-----|--|
| POF | User instruction ENDURA STYLE PLATE WALL   |
|     | Tender documents Tender Text 4058075477872 |



#### **LOGISTICAL DATA**

| Product code  | Packaging unit (Pieces/Unit) | Dimensions (length x width x height) | Gross weight | Volume               |
|---------------|------------------------------|--------------------------------------|--------------|----------------------|
| 4058075477872 | Folding box<br>1             | 65 mm x 185 mm x 290 mm              | 756.00 g     | 3.49 dm <sup>3</sup> |
| 4058075477889 | Shipping box<br>4            | 310 mm x 280 mm x 205 mm             | 3.39 g       | 17.79 dm³            |

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

#### **DISCLAIMER**

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.