

PRODUCT DATASHEET ENDURA GARDEN 9 Dot 6W

ENDURA GARDEN DOT | Decorative light dots for outdoor use





TECHNICAL DATA

Electrical data

Nominal wattage	6.00 W
Operating mode	Mains voltage
Nominal voltage	220240 V
Power factor λ	> 0,5

Photometrical data

Color temperature	3000 K
Luminous flux	380 lm
Luminous efficacy	63 lm/W
Light color	Warm White
Standard deviation of color matching	≤6 sdcm
Color rendering index Ra	≥80

Light technical data

Beam angle	33.00 °

Dimensions & weight



Diameter	23.00 mm
Height	96.00 mm
Width	23.00 mm
Product weight	340.00 g

Colors & materials

Body material	Polycarbonate (PC)
Product color	Clear
Cover material	Polycarbonate (PC)

Temperatures & operating conditions

Ambient temperature range	-20+40 °C

Lifespan

Number of switching cycles	12500
Lifespan L70/B50 at 25 °C	25000 h

Additional product data

	Mounting type	Ground spike
	Mounting location	Ground
Ī	With light source	Yes

Capabilities

Dimmable	No
Type of connection	Plug type C (EU)
LEDmod replaceable	Not replaceable

Certificates & standards

Protection class	П
Type of protection	IP65
Standards	CE / EAC / REACH / RoHS

DOWNLOAD DATA

	DOWNLOAD DATA
POF	User instruction ENDURA GARDEN DOT
	Tender documents Tender Text 4058075478411

LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4058075478411	Folding box 1	132 mm x 122 mm x 104 mm	388.00 g	1.67 dm³
4058075478428	Shipping box 4	278 mm x 258 mm x 129 mm	1855.00 g	9.25 dm³

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

DISCLAIMER



Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.

