

# PRODUCT DATASHEET

## ENDURA GARDEN 3 Dot extension 2,1 W

ENDURA GARDEN DOT | Decorative light dots for outdoor use



TECHNICAL DATA

Electrical data

Nominal wattage	2.10 W
Operating mode	Mains voltage
Nominal voltage	220...240 V
Power factor $\lambda$	> 0,5


Photometrical data

Color temperature	3000 K
Luminous flux	110 lm
Luminous efficacy	52 lm/W
Light color	Warm White
Standard deviation of color matching	$\leq 6$ sdcm
Color rendering index Ra	$\geq 80$

Light technical data

Beam angle	33.00 °
------------	---------

Dimensions & weight



Diameter	23.00 mm
Height	96.00 mm
Width	23.00 mm
Product weight	80.00 g

Colors & materials

Body material	Polycarbonate (PC)
Product color	Clear
Cover material	Polycarbonate (PC)

Temperatures & operating conditions



Ambient temperature range	-20...+40 °C
---------------------------	--------------

### Lifespan

Number of switching cycles	12500
Lifespan L70/B50 at 25 °C	25000 h

### Additional product data

Mounting type	Ground spike
Mounting location	Ground
With light source	Yes



### Capabilities

Dimmable	No
Type of connection	Plug type C (EU)
LEDmod replaceable	Not replaceable

### Certificates & standards

Protection class	III
Type of protection	IP65
Standards	CE / EAC / REACH / RoHS

### DOWNLOAD DATA

DOWNLOAD DATA	
	User instruction ENDURA GARDEN DOT
	Tender documents Tender Text 4058075478510

### LOGISTICAL DATA

Product code	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Gross weight	Volume
4058075478510	Folding box 1	102 mm x 44 mm x 109 mm	100.00 g	0.49 dm <sup>3</sup>
4058075478527	Shipping box 4	180 mm x 125 mm x 120 mm	534.00 g	2.70 dm <sup>3</sup>

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.



## DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.