

PRODUCT DATASHEET

SST CLAS B 25 2.8 W/2700K E14

LED Retrofit CLASSIC B DIM | Dimmable LED lamps, classic bulb shape



AREAS OF APPLICATION

- Domestic applications
- General illumination
- Outdoor use in outdoor luminaires only (minimum IP65)
- Perfect for decorative installations

PRODUCT BENEFITS

- Lamps with innovative LED "filament" technology
- Very low energy consumption
- Instant 100 % light, no warm-up time
- Can be easily fitted instead of ordinary light bulbs
- Design, dimensions, luminous flux comparable to an incandescent lamp

PRODUCT FEATURES

- LED lamps for line voltage
- Dimmable (with many common dimmers, see also www.ledvance.com/dim)
- Mercury-free lamps
- Beam angle: up to 300°
- Lifetime: up to 15,000 h
- Energy efficiency class: A++



TECHNICAL DATA

Electrical data

| | |
|--|-------------|
| Rated wattage | 2.80 W |
| Nominal wattage | 2.80 W |
| Nominal voltage | 220...240 V |
| Max. lamp no. on circuit break. 10 A (B) | 696 |
| Max. lamp no. on circuit break. 16 A (B) | 1115 |
| Operating frequency | 50...60 Hz |
| Power factor λ | > 0.70 |
| Claimed equiv. conventional lamp power | 25 W |


Photometrical data

| | |
|---|---------------------------|
| Nominal luminous flux | 250 lm |
| Rated luminous flux | 250 lm |
| Lumen main.fact.at end of nom.life time | 0.70 |
| Light color (designation) | Warm White |
| Color temperature | 2700 K |
| Luminous flux | 250 lm |
| Color rendering index Ra | ≥ 80 |
| Standard deviation of color matching | ≤ 6 sdc _m |
| Rated color temperature | 2700 K |

Light technical data

| | |
|---------------------|----------|
| Warm-up time (60 %) | < 0.50 s |
| Starting time | < 0.5 s |

Dimensions & weight



| | |
|----------------|---------|
| Overall length | 97.0 mm |
| Diameter | 35.0 mm |

| | |
|-------------------|---------|
| Outer bulb | B35 |
| Length | 97.0 mm |

Temperatures & operating conditions

| | |
|---|--------------|
| Ambient temperature range | -20...+40 °C |
| Maximum temperature at tc test point | 50 °C |

Lifespan

| | |
|---|---------|
| Nominal lamp life time | 15000 h |
| Rated lamp life time | 15000 h |
| Number of switching cycles | 100000 |
| Lumen maintenance at end of service life | 0.70 |

Additional product data

| | |
|------------------------------------|--|
| Base (standard designation) | E14 |
| Mercury content | 0.0 mg |
| Mercury-free | Yes |
| Design / version | Frosted |
| Show WEEE picto | Yes |
| Product remark | All technical parameters apply to the entire lamp/Due to the complex production process for light-emitting diodes, the typical values shown for the technical LED parameters are purely statistical values that do not necessarily match the actual technical parameters of each individual product, which can vary from the typical value/LED lamps contain several electronic components. Under unfavourable conditions these can lead to acoustic noise. In case of resonance even low noise can cause audible effect. Possible factors influencing this are the installation, the design of the lamp holder and the luminaire (acoustic resonance effect) as well as the dimmer or the transformer (harmonics or electronic resonance) |

Capabilities

| | |
|-----------------|-----|
| Dimmable | Yes |
|-----------------|-----|

Certificates & standards

| | |
|--------------------------------|-------------|
| Energy efficiency class | A++ |
| Energy consumption | 3 kWh/1000h |

Country-specific categorizations

| | |
|------------------------|-------------------------------|
| ILCOS | DRBB/F-3,2-827-220-240-E14-25 |
| Order reference | LEDSCLB25D2,8W/ |

LOGISTICAL DATA

| Product code | Packaging unit (Pieces/Unit) | Dimensions (length x width x height) | Gross weight | Volume |
|---------------|------------------------------|--------------------------------------|--------------|----------------------|
| 4058075051867 | Blister 1 | 42 mm x 140 mm x 120 mm | 28.00 g | 0.71 dm ³ |
| 4058075051874 | Shipping carton box 6 | 262 mm x 153 mm x 136 mm | 280.00 g | 5.45 dm ³ |
| 4058075054363 | Folding carton box 1 | 39 mm x 39 mm x 109 mm | 22.00 g | 0.17 dm ³ |
| 4058075054370 | Shipping carton box 10 | 215 mm x 90 mm x 118 mm | 283.00 g | 2.28 dm ³ |

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

DISCLAIMER

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.