



General Data

Article No.	OTNA4034
Code	DRIVER DC 30W/700mA IP20
Product EAN	4003556010864
Customs tariff no.	85044082
Box quantitiy (pcs.)	48
EAN Box	4003556410862
Gross weight of box in kg	6.85
Length of box in m	0.385
Width of box in m	0.285
Height of box in m	0.21
ETIM class	EC002710
ETIM class name	LED driver
Weight	140 g
Product status	<div></div> Active

Electric Parameters

Rated value output power max.	31,5 W
Power factor	≥0,95
Output voltage	33-42 V
Surge voltage resistance (L - N)	3,75 kV
Output current	700-700 mA
Supply frequency	50/60 Hz
dimnable	No

Driver for DC-LED lamps or modules

DRIVER 30W/700mA IP20

Radium

Service Life

Service life	70000 h
Tc Temperature max.	75 °C

Specification

Mean efficiency	≥87% %
Length	195 mm
Length	195 mm
Height	20 mm
Width	30 mm
Material	metal
Weight	140 g

Notes on Operation

Degree of protection (IP)	IP20
Type of connection	spring clamp
Ambient temperatures	-30...+50
Tc Temperature max.	75 °C

Notes

External constant current driver for installation in luminaire (e.g. for DC LED tubes), not dimmable, indoor use.

Please, refer to www.radium.de/recycling for notes on disposal of burned-out lamps as well as lamp breakage.

The "lifespan L70" described for LED lamps indicates the number of hours when the luminous flux has decreased to 70% of its initial value.

The optimal field 'info about service life' contains the frame conditions according to standards based on which the specific service life has been determined. So, for example, "12B50, 50Hz" means that the mean service life (B50) has been determined with a 12h switching cycle at mains (frequency 50Hz), "3B50, HF" is based on a 3h switching cycle at electronic control gear (high frequency).

Special features



All technical data without guarantee.