

Blacklight BL368 Linear T12

F40W T12 BL368 48"

0000099



Range Features

- Features
- BL368 tubes emit an upgraded highly concentrated radiation with peak around 368 nm. Flying insects eye sensitivity is generally at or near this frequency
- 100% improvement in effectiveness (at 368nm)
- Depreciation of UV-A output over time is significantly reduced (80% at 5000hrs of original 100 hour output)
- Performs longer and better throughout the insect season
- Same shape, structural and electrical characteristics and control circuits as standard T12,T8 or T5 tubes
- Applications
- Insect traps, insect attraction is strongly increased
- Restaurants, kitchens, food shops, supermarkets
- Diazo printing machines
- Photo Polymerisation
- Chemical processing
- Mineral detection
- Various technical applications
- Directions for use
- Maximum exposure limits are set by EN60335-2-59:1997 at an effective 1.0 milliWatt per metre squared (1.0 mW/m²) measured at a distance of 1 metre originally based on the recommendations of the National Radiological Protection Board in the UK. The irradiance value for a single BL368-lamp measured without reflector and/or fixture, in free air at 25 celsius, is varying between 0.2 and 0.4 mW/m² depending on the wattage



PRODUCT OVERVIEW

Lampenoberfläche	Beschichtet
Lampenform	Tubular
Farbtemperatur (K)	UV-A lamp
Dimmbar	YES
EAN-Code	5410288000992
Verschluss/Socket	G13
Typ	BL368
Watt (Nennleistung) (W)	40
Bestellnummer	0000099
Technologie	Fluorescent
Spannung (V)	103

DATENTABELLE

Allgemeine Daten

Blacklight BL368 Linear T12

F40W T12 BL368 48"

0000099

Betriebsgerät erforderlich	Ja
Lampenoberfläche	Beschichtet
Lampenform	Tubular
Dimmbar	YES
EAN-Code	5410288000992
Allgemeiner Einsatz	Retail; Hospitality; Logistics and Industry; Museums; Education; Office; Residential & Consumer
Einsatzzweck	Special lighting
Verschluss/Socket	G13
Typ	BL368
Bestellnummer	0000099
Lange Bezeichnung	<p>Features</p> <p>BL368 tubes emit an upgraded highly concentrated radiation with peak around 368 nm. Flying insects eye sensitivity is generally at or near this frequency</p> <p>100% improvement in effectiveness (at 368nm)</p> <p>Depreciation of UV-A output over time is significantly reduced (80% at 5000hrs of original 100 hour output)</p> <p>Performs longer and better throughout the insect season</p> <p>Same shape, structural and electrical characteristics and control circuits as standard T12,T8 or T5 tubes</p> <p>Applications</p> <p>Insect traps, insect attraction is strongly increased</p> <p>Restaurants, kitchens, food shops, supermarkets</p> <p>Diazo printing machines</p> <p>Photo Polymerisation</p> <p>Chemical processing</p> <p>Mineral detection</p> <p>Various technical applications</p> <p>Directions for use</p> <p>Maximum exposure limits are set by EN60335-2-59:1997 at an effective 1.0 milliWatt per metre squared (1.0 mW/m²) measured at a distance of 1 metre originally based on the recommendations of the National Radiological Protection Board in the UK. The irradiance value for a single BL368-lamp measured without reflector and/or fixture, in free air at 25 celsius, is varying between 0.2 and 0.4 mW/m² depending on the wattage</p>
Produktname	F40W T12 BL368 48"
Lampen für spezielle Einsatzbereiche	Yes
Technologie	Fluorescent
Menge/Verpackungseinheit	25
E-Nummer FI	4940428
Optische Daten	
Farbtemperatur (K)	UV-A lamp
Elektrische Daten	
Watt (Nennleistung) (W)	40

Blacklight BL368 Linear T12

F40W T12 BL368 48"


0000099

Spannung (V) 103



Physikalische Daten

Verpackungsbezeichnung	Box/Sleeve
Gewicht (kg)	0.28

TECHNISCHE ZEICHNUNGEN



G13



max 25,78

