

Blacklight BL368 Toughcoat T8

F15W T8 BL 368 Toughcoat™

0000124



Range Features

- Excellent fragment retention in the event of breakage
- The protective FEP coating meets the IEC60068-2-75 Pendulum Hammer test (5 Joule) and the 4m drop test, demonstrating excellent glass retention in the event of accidental lamp breakage
- The 97% UV-A transmission of FEP maintains maximum insect attraction
- No discolouration or yellowing of shatter resistant coating during the entire lamp life (> 10,000 hrs)
- The FEP material does not degrade during life. Versions employing PET coatings become brittle, and may not contain fragments. PET is also less transparent for UV- radiation
- The coating withstands up to 200°C in both open and enclosed IP65 fittings.
- The melting temperature is 260°C
- Meets all necessary regulations for resistance to heat and fire, and does not support combustion when exposed to naked flame or excessive heat. It passes the 850°C Glow Wire Test
- Satisfies the requirements of the International Food Standard (IFS 2004)
- FDA approved, in compliance with 21CFR177.1550 Regulatory Compliance Status
- Satisfies the requirements of the BRC (British Retail Consortium) leading supermarkets global standard. In paragraph 3.2.2.6.2 it states All bulbs and strip lights, including those on electric fly killer units, where they constitute a risk to products, shall be protected by shatterproof plastic diffusers, sleeve covers or with a shatterproof protective coating
- Applications
- Insect attraction in restaurants, kitchens, food shops, supermarkets
- Food processing plants
- Pharmaceutical industry
- The risk of glass and mercury contamination is strongly decreased
- Help to avoid injury and loss of production time



PRODUCT OVERVIEW

Lamp finish	FEP Toughcoated
Lamp shape	Tubular
Colour temperature (K)	UV-A lamp
Dimmable	Yes
EAN code	5410288001241
Cap/Base	G13
Type	BL368
Watt (Nominal) (W)	15
Ordering number	0000124
Technology	Fluorescent
Voltage (V)	55

Blacklight BL368 Toughcoat T8

F15W T8 BL 368 Toughcoat™

0000124

DATA TABLE

General data

Control gear required	Yes
Lamp finish	FEP Toughcoated
Lamp shape	Tubular
Dimmable	Yes
EAN code	5410288001241
General application	Retail; Hospitality; Logistics and Industry; Museums; Education; Office; Residential & Consumer
Intended purpose	Special lighting
Cap/Base	G13
Lamp mercury content (mg)	10
Type	BL368
Ordering number	0000124

Blacklight BL368 Toughcoat T8

F15W T8 BL 368 Toughcoat™

0000124

Range features

Excellent fragment retention in the event of breakage
 The protective FEP coating meets the IEC60068-2-75 Pendulum Hammer test (5 Joule) and the 4m drop test, demonstrating excellent glass retention in the event of accidental lamp breakage
 The 97% UV-A transmission of FEP maintains maximum insect attraction
 No discolouration or yellowing of shatter resistant coating during the entire lamp life (> 10,000 hrs)
 The FEP material does not degrade during life. Versions employing PET coatings become brittle, and may not contain fragments. PET is also less transparent for UV- radiation
 The coating withstands up to 200°C in both open and enclosed IP65 fittings.
 The melting temperature is 260°C
 Meets all necessary regulations for resistance to heat and fire, and does not support combustion when exposed to naked flame or excessive heat. It passes the 850°C Glow Wire Test
 Satisfies the requirements of the International Food Standard (IFS 2004)
 FDA approved, in compliance with 21CFR177.1550 Regulatory Compliance Status
 Satisfies the requirements of the BRC (British Retail Consortium) leading supermarkets global standard. In paragraph 3.2.2.6.2 it states All bulbs and strip lights, including those on electric fly killer units, where they constitute a risk to products, shall be protected by shatterproof plastic diffusers, sleeve covers or with a shatterproof protective coating

Applications

Insect attraction in restaurants, kitchens, food shops, supermarkets
 Food processing plants
 Pharmaceutical industry
 The risk of glass and mercury contamination is strongly decreased
 Help to avoid injury and loss of production time

Product name	F15W T8 BL 368 Toughcoat™
Special purpose lamp	Yes
Technology	Fluorescent
Sales pack quantity	25
E-number FI	4940430

Optical data

Colour temperature (K)	UV-A lamp
-------------------------------	-----------

Physical data

Max. Lamp Diameter (mm) - D	26
Lamp Length (mm) - C/L	451.6
Length base to base (mm) - A	437.4
Length base to pin Min-Max - B	442.1-444.5

Blacklight BL368 Toughcoat T8

F15W T8 BL 368 Toughcoat™

0000124

Single packaging type	Box/Sleeve
Weight (kg)	0.06
Outer package dimensions (L x W x H) (cm)	48.00 x 15.50 x 15.00
Single package dimensions (L x W x H) (cm)	45.20 x 2.90 x 2.80

Electrical data

Watt (Nominal) (W)	15
Watt (Rated) (W)	15
Voltage (V)	55

TECHNICAL DRAWINGS

G13

