

Grolux T8

F25W/30/GRO

0001679



Range Features

- High level of blue and red radiation helps promote healthy plant growth
- Strengthens the natural colours of aquatic plants and fish in aquariums
- Promotes the process of photo-synthesis in plants
- Oldest, but most optimal light colour for plants and aquaria
- Applications
- For lighting of fresh water aquariums
- Complete or additional artificial lighting of plants
- Recommended for use in greenhouses, indoor gardens, flower shows and conservatories



PRODUCT OVERVIEW

Lamp finish	Coated
Lamp shape	Tubular
Dimmable	Yes
EAN code	5410288016795
Cap/Base	G13
Type	GroLux
Watt (Nominal) (W)	25
Ordering number	0001679
Technology	Fluorescent
Voltage (V)	84

DATA TABLE

General data

Average life (Nominal) (h)	10000
Control gear required	Yes
Lamp finish	Coated
Lamp shape	Tubular
Dimmable	Yes
EAN code	5410288016795
Fixture rating	Open
General application	Retail; Hospitality; Logistics and Industry; Museums; Education; Office; Residential & Consumer
IEC Reference	Special lighting
IEC Reference 2	IEC 61195
Intended purpose	Special lighting
Cap/Base	G13

Grolux T8

F25W/30/GRO

0001679

Lamp mercury content (mg)	10
Type	GroLux
Ordering number	0001679
Range features	<p>High level of blue and red radiation helps promote healthy plant growth</p> <p>Strengthens the natural colours of aquatic plants and fish in aquariums</p> <p>Promotes the process of photo-synthesis in plants</p> <p>Oldest, but most optimal light colour for plants and aquaria</p> <p>Applications</p> <p>For lighting of fresh water aquariums</p> <p>Complete or additional artificial lighting of plants</p> <p>Recommended for use in greenhouses, indoor gardens, flower shows and conservatories</p>
Product name	F25W/30/GRO
Special purpose lamp	Yes
Technology	Fluorescent
Transformer required	No
Sales pack quantity	25
E-number SE	8356671

Electrical data

Current (A)	0.36
Watt (Nominal) (W)	25
Watt (Rated) (W)	25
Voltage (V)	84

Physical data

Max. Lamp Diameter (mm) - D	26
Lamp Length (mm) - C/L	756.4
Length base to base (mm) - A	742.2
Length base to pin Min-Max - B	746.9-749.3
Single packaging type	Box/Sleeve
Weight (kg)	0.10
Outer package dimensions (L x W x H) (cm)	78.50 x 15.50 x 15.00
Single package dimensions (L x W x H) (cm)	75.70 x 2.90 x 2.80

TECHNICAL DRAWINGS

Grolux T8
F25W/30/GRO
0001679

