

Blacklight BL368 Linear T8

F25WT8/18"/BL368 SYLVANIA

0002166



Range Features

- BL368 tubes emit an upgraded highly concentrated radiation with peak around 368 nm. Flying insects eye sensitivity is generally at or near this frequency
- 100% improvement in effectiveness (at 368nm)
- Depreciation of UV-A output over time is significantly reduced (80% at 5000hrs of original 100 hour output)
- Performs longer and better throughout the insect season
- Same shape, structural and electrical characteristics and control circuits as standard T12,T8 or T5 tubes
- Applications
- Insect traps, insect attraction is strongly increased
- Restaurants, kitchens, food shops, supermarkets
- Diazo printing machines
- Photo Polymerisation
- Chemical processing
- Mineral detection
- Various technical applications
- Directions for use
- Maximum exposure limits are set by EN60335-2-59:1997 at an effective 1.0 milliWatt per metre squared (1.0 mW/m²) measured at a distance of 1 metre originally based on the recommendations of the National Radiological Protection Board in the UK. The irradiance value for a single BL368-lamp measured without reflector and/or fixture, in free air at 25 celsius, is varying between 0.2 and 0.4 mW/m² depending on the wattage



PRODUCT OVERVIEW

Lamp finish	Coated
Lamp shape	Tubular
Colour temperature (K)	UV-A lamp
Dimmable	Yes
EAN code	5410288021669
Cap/Base	G13
Type	BL368
Watt (Nominal) (W)	25
Ordering number	0002166
Technology	Fluorescent
Voltage (V)	38

DATA TABLE

General data

Control gear required	Yes
-----------------------	-----

Blacklight BL368 Linear T8

F25WT8/18"/BL368 SYLVANIA

0002166

Lamp finish	Coated
Lamp shape	Tubular
Dimmable	Yes
EAN code	5410288021669
General application	Retail; Hospitality; Logistics and Industry; Museums; Education; Office; Residential & Consumer
Intended purpose	Special lighting
Cap/Base	G13
Lamp mercury content (mg)	10
Type	BL368
Ordering number	0002166

BL368 tubes emit an upgraded highly concentrated radiation with peak around 368 nm. Flying insects eye sensitivity is generally at or near this frequency

100% improvement in effectiveness (at 368nm)

Depreciation of UV-A output over time is significantly reduced (80% at 5000hrs of original 100 hour output)

Performs longer and better throughout the insect season

Same shape, structural and electrical characteristics and control circuits as standard T12,T8 or T5 tubes

Applications

Insect traps, insect attraction is strongly increased

Restaurants, kitchens, food shops, supermarkets

Diazo printing machines

Photo Polymerisation

Chemical processing

Mineral detection

Various technical applications

Directions for use

Maximum exposure limits are set by EN60335-2-59:1997 at an effective 1.0 milliWatt per metre squared (1.0 mW/m²) measured at a distance of 1 metre originally based on the recommendations of the National Radiological Protection Board in the UK. The irradiance value for a single BL368-lamp measured without reflector and/or fixture, in free air at 25 celsius, is varying between 0.2 and 0.4 mW/m² depending on the wattage

Range features

Product name	F25WT8/18"/BL368 SYLVANIA
Special purpose lamp	Yes
Technology	Fluorescent
Sales pack quantity	25

Optical data

Colour temperature (K)	UV-A lamp
-------------------------------	-----------

Electrical data

Current (A)	0.6
Watt (Nominal) (W)	25

Blacklight BL368 Linear T8

F25WT8/18"/BL368 SYLVANIA

0002166

Watt (Rated) (W)	25
Voltage (V)	38

Physical data

Max. Lamp Diameter (mm) - D	26
Lamp Length (mm) - C/L	451.6
Length base to base (mm) - A	437.4
Length base to pin Min-Max - B	442.1-444.5
Single packaging type	Box/Sleeve
Weight (kg)	0.06

TECHNICAL DRAWINGS

