

Linear Double Ended ECO 78/118mm

DE 78MM ECO 230V 48W R7S SV1

0021529



Range Features

- Xenon technology
- Sparkling light output
- Less CO2 emissions
- Less heat generation
- Transformer free operation
- Filament support method patented
- Average rated life 1000hrs or 2000hrs - 20% energy savings compared to standard halogen double ended lamps with same light output



PRODUCT OVERVIEW

Lamp finish	clear
Lamp shape	Linear
Colour temperature (K)	2900
CRI (Ra)	100
Dimmable	Yes
EAN code	5410288215297
Energy class	D
Cap/Base	R7s
Beam angle(°)	na
Type	Linear Double Ended
Watt (Nominal) (W)	48
Light colour	829 Warm white
Ordering number	0021529
Average life (Rated) (h)	2000
Luminous flux (Rated) (lm)	750
Technology	Halogen
Voltage (V)	230

DATA TABLE

General data

Average life (Nominal) (h)	2000
Control gear required	No
Lamp finish	clear
Lamp shape	Linear
Dimmable	Yes
EAN code	5410288215297
Energy class	D

Linear Double Ended ECO 78/118mm

DE 78MM ECO 230V 48W R7S SV1

0021529

Energy saving lamp	No
Fixture rating	Enclosed
General application	Residential & Consumer; Hospitality; Logistics & Industry
IEC Reference	IEC 60357
IEC Reference 2	IEC 60432-3
Intended purpose	General lighting
Cap/Base	R7s
Lamp mercury content (mg)	0
Type	Linear Double Ended
No. of switching cycles before premature failure (min)	> 8000
Optimal operating condition (°C)	25
Ordering number	0021529

Xenon technology
Sparkling light output
Less CO2 emissions
Less heat generation
Transformer free operation
Filament support method patented
Average rated life 1000hrs or 2000hrs - 20% energy savings compared to standard halogen double ended lamps with same light output

Range features

Product name	DE 78MM ECO 230V 48W R7S SV1
Average life (Rated) (h)	2000
Special purpose lamp	No
Starting time (max) (s)	0.01
Technology	Halogen
Transformer required	No
Sales pack quantity	10
Warm-up time to 60% of full light (max) (s)	Instant full light

Optical data

Colour temperature (K)	2900
CRI (Ra)	100
Beam angle(°)	na
Light colour	829 Warm white
Lumen maintenance at end of nominal life (%)	80
Luminous flux (Nominal) (lm)	750
Luminous flux (Rated) (lm)	750
Suitable for accent lighting	No

Electrical data

kWh per 1000 hours burning time	48
--	----

Linear Double Ended ECO 78/118mm

DE 78MM ECO 230V 48W R7S SV1

0021529

Lamp power factor	1
Watt (Nominal) (W)	48
Watt (Rated) (W)	48
Voltage (V)	230

Physical data

Max. Lamp Diameter (mm) - D	12
Lamp Length (mm) - C/L	80
Single packaging type	Box/Sleeve
Weight (kg)	0.01
Outer package dimensions (L x W x H) (cm)	24.50 x 14.50 x 13.50
Single package dimensions (L x W x H) (cm)	12.00 x 1.80 x 2.10

TECHNICAL DRAWINGS



Linear Double Ended ECO 78/118mm

DE 78MM ECO 230V 48W R7S SV1

0021529

