

## Blacklight BL368 Compact

Lynx-L 36W BL368

0025710



### Range Features

- Features
- These BL368 tubes emit an upgraded highly concentrated radiation with peak around 368nm. Flying insect - eye sensitivity is generally at or near this frequency
- 100% improvement in effectiveness (at 368nm)
- Depreciation of UV-A output over time is significantly reduced (80% at 5000hrs of original 100 hour output)
- Performs longer and better throughout the insect season
- 
- Directions for use
- Maximum exposure limits are set by EN60335 2-59:1997 at an effective 1,0 milliWatt per metre squared (1,0 mW/m) measured at a distance of 1 metre - originally based on the recommendations of the National Radiological Protection Board in the UK. The irradiance value for a single BL BL368-lamp measured without reflector and/or fixture, in free air at 25 celsius, is varying between 0,2 and 0,4 mW/m depending on the wattage



### PRODUCT OVERVIEW

Farbtemperatur (K)	UV-A lamp
EAN-Code	5410288257105
Verschluss/Socket	2G11
Typ	BL368
Watt (Nennleistung) (W)	36
Bestellnummer	0025710
Technologie	Fluorescent
Spannung (V)	106

### DATENTABELLE

#### Optische Daten

Farbtemperatur (K)	UV-A lamp
--------------------	-----------

#### Allgemeine Daten

EAN-Code	5410288257105
Allgemeiner Einsatz	Retail; Hospitality; Logistics and Industry; Museums; Education; Office; Residential & Consumer
Einsatzzweck	Special lighting
Verschluss/Socket	2G11
Typ	BL368
Bestellnummer	0025710

## Blacklight BL368 Compact

Lynx-L 36W BL368

0025710

<b>Lange Bezeichnung</b>	<p>Features</p> <p>These BL368 tubes emit an upgraded highly concentrated radiation with peak around 368nm. Flying insect - eye sensitivity is generally at or near this frequency 100% improvement in effectiveness (at 368nm) Depreciation of UV-A output over time is significantly reduced (80% at 5000hrs of original 100 hour output) Performs longer and better throughout the insect season</p> <p>Directions for use</p> <p>Maximum exposure limits are set by EN60335 2-59:1997 at an effective 1,0 milliWatt per metre squared (1,0 mW/m) measured at a distance of 1 metre - originally based on the recommendations of the National Radiological Protection Board in the UK. The irradiance value for a single BL BL368-lamp measured without reflector and/or fixture, in free air at 25 celsius, is varying between 0,2 and 0,4 mW/m depending on the wattage</p>
<b>Produktname</b>	Lynx-L 36W BL368
<b>Lampen für spezielle Einsatzbereiche</b>	Yes
<b>Technologie</b>	Fluorescent
<b>Menge/Verpackungseinheit</b>	10
<b>E-Nummer FI</b>	4940710

### Elektrische Daten

<b>Watt (Nennleistung) (W)</b>	36
<b>Spannung (V)</b>	106

### Physikalische Daten

<b>Verpackungsbezeichnung</b>	Box/Sleeve
<b>Gewicht (kg)</b>	0.12
<b>Outer package dimensions (L x W x H) (cm)</b>	48.00 x 15.00 x 11.00
<b>Single package dimensions (L x W x H) (cm)</b>	46.00 x 4.60 x 2.70

## TECHNISCHE ZEICHNUNGEN

