

Aqua arc

HSI-TD 250W AquaArc

0021050



Range Features

- High light output and good efficiency
- High colour rendering
- Very high colour stability over the whole lamp life
- High colour temperature (10000K)
- Point-source of light creates attractive shadow effect of water ripples on the aquarium bed
- Applications
- For use in fresh and seawater aquaria
- Strong directional light which penetrates deep into large tanks
- Lifelike appearance of fish, corals and plants
- Directions for use
- Burning position: horizontal $\pm 45^\circ$
- External ignitor only
- Only use in luminaires fitted with protective cover glass
- Ensure the lamp envelope is cleaned of finger prints before use
- Lamps should be operated with the arc tube tip-off pointing up-see instructions supplied with lamp
- This lamp emits UV-radiation. Avoid exposure to skin and eyes
- Not suitable for household room illumination



PRODUCT OVERVIEW

Lampenoberfläche	Clear
Lampenform	Linear
Farbtemperatur (K)	9000
EAN-Code	5410288210506
Verschluss/Socket	Rx7s-24
Typ	HSI-TD
Watt (Nennleistung) (W)	250
Bestellnummer	0021050
Nutzbarer Lichtstrom (Nennwert) (lm)	14000
Spannung (V)	100

DATENTABELLE

Allgemeine Daten

Mittlere Lebensdauer (Nennwert) (h)	9000
Betriebsgerät erforderlich	Yes
Lampenoberfläche	Clear
Lampenform	Linear
EAN-Code	5410288210506
Leuchtennennwert	Enclosed

Aqua arc

HSI-TD 250W AquaArc

0021050

Allgemeiner Einsatz	Retail; Hospitality; Logistics and Industry; Museums; Education; Office; Residential & Consumer
IEC-Referenz	IEC 61167
IEC-Referenz 2	IEC 62035
Verschluss/Socket	Rx7s-24
Quecksilbergehalt der Lampe (mg)	12.5
Typ	HSI-TD
Bestellnummer	0021050

High light output and good efficiency
 High colour rendering
 Very high colour stability over the whole lamp life
 High colour temperature (10000K)
 Point-source of light creates attractive shadow effect of water ripples on the aquarium bed

Applications
 For use in fresh and seawater aquaria
 Strong directional light which penetrates deep into large tanks
 Lifelike appearance of fish, corals and plants

Directions for use
 Burning position: horizontal $\pm 45^\circ$
 External ignitor only
 Only use in luminaires fitted with protective cover glass
 Ensure the lamp envelope is cleaned of finger prints before use
 Lamps should be operated with the arc tube tip-off pointing up-see instructions supplied with lamp
 This lamp emits UV-radiation. Avoid exposure to skin and eyes
 Not suitable for household room illumination

Lange Bezeichnung

Produktname	HSI-TD 250W AquaArc
Lampen für spezielle Einsatzbereiche	Yes
Transformator erforderlich	No
Menge/Verpackungseinheit	10

Optische Daten

Farbwertanteil Y	0.323
Farbtemperatur (K)	9000
Nutzbarer Lichtstrom (Nennwert) (lm)	14000

Elektrische Daten

Stromstärke (A)	3
Watt (Nennleistung) (W)	250
Watt (Nennwert) (W)	250
Spannung (V)	100

Physikalische Daten

Lampendurchmesser (mm) – D	27.5
Lampenlänge (mm) – C/L	161.6

Aqua arc

HSI-TD 250W AquaArc

0021050

Verpackungsbezeichnung	Box/Sleeve
Gewicht (kg)	0.05
Outer package dimensions (L x W x H) (cm)	28.00 x 24.00 x 12.50
Single package dimensions (L x W x H) (cm)	3.20 x 3.20 x 21.00

TECHNISCHE ZEICHNUNGEN

RX7s-24

