

64382 HLX-A 200-15

Halogen lamps, current-controlled with PK30d base

Areas of application

- Airfield lighting



Product benefits

- Reduced operation and maintenance costs due to long lifetime
- Instant and constant light output over the lamp life
- Flicker-free operation
- Mercury-free

Product features

- Dimmable
- Available with connector combinations A, B, C/Z on request
- Infrared radiation output that provides light in the worst of conditions




Product datasheet

Technical data

Electrical data

| | |
|-----------------|----------|
| Nominal wattage | 200.00 W |
| Nominal voltage | 30.3 V |
| Lamp current | 6.6 A |

Dimensions & weight



| | |
|---|----------|
| Diameter | 13.5 mm |
| Length | 57.0 mm |
| Length with base excl. base pins/connection | 36.00 mm |
| Light center length (LCL) | 20.0 mm |

Lifespan

| | |
|----------|--------|
| Lifespan | 1500 h |
|----------|--------|

Additional product data

| | |
|-----------------------------|-------|
| Base (standard designation) | PK30d |
|-----------------------------|-------|

Capabilities

| | |
|------------------|-------------------|
| Burning position | s90 ¹⁾ |
|------------------|-------------------|

¹⁾ Despite transverse filament, can be inclined at any angle in s90 position

Country specific categorizations

| | |
|-----------------|-----------------|
| LIF | J1/84 |
| Order reference | 64382 HLX-A 200 |

Country specific information

Product datasheet

| Product code | METEL code | SEG-No. | STK-Number | UK Org |
|---------------|--------------|---------|------------|--------|
| 4008321345738 | OSRH64382HLX | - | - | - |

Product datasheet

Safety advice

To prevent personal injury or damage to property, halogen lamps may only be operated in suitable luminaires designed with suitable mechanisms (protective shields, grids, etc.) to ensure that in the event of a lamp bursting no parts/shards can escape and that during operation no ultraviolet radiation can escape. There must also be a warning sign to indicate that the lamps give off high levels of heat. Detailed information is available on request.

Logistical Data

| Product code | Product description | Packaging unit (Pieces/Unit) | Dimensions (length x width x height) | Volume | Gross weight |
|---------------|---------------------|------------------------------|--------------------------------------|-----------------------|--------------|
| 4008321345738 | 64382 HLX-A 200-15 | Folding carton box 1 | 71 mm x 33 mm x 37 mm | 0.09 dm ³ | 23.00 g |
| 4008321345745 | 64382 HLX-A 200-15 | Shipping carton box 100 | 341 mm x 191 mm x 154 mm | 10.03 dm ³ | 2300.00 g |

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

References / Links

For more information on airfield lamps see the brochure:

"The reliable guiding stars - Effective solutions for airfield lighting: Tungsten halogen lamps and LED light sources".

Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.
