




Technical data

Electrical data

Lamp wattage	20...315 W
Nominal voltage	220...240 V
Mains frequency	50 Hz
System wattage	315.00 W

Dimensions & weight



Length	153.0 mm
Width	54.0 mm
Height	36.0 mm
Mounting hole spacing, width	15.0 mm
Mounting hole spacing, length	146.0 mm
Product weight	137.00 g

Temperatures & operating conditions

Ambient temperature range	0...+45 °C
---------------------------	------------

Additional product data

Design / version	Compact with cable clamp
------------------	--------------------------

Capabilities

Dimming method	Trailing-edge dimmer
Dimming interface	DALI / Touch DIM
Max. cable length to lamp/LED module	100 m
Dimmable	Yes
Dimming range	0.1...100 % <sup>1)</sup>

<sup>1)</sup> Depends on the lamp type (please see [www.osram.com/dim](http://www.osram.com/dim))

# Product datasheet





## Certificates & standards

Type of protection	IP20
--------------------	------

## Equipment / Accessories

- Suitable for all OSRAM HALOTRONIC and ET-PARROT ECGs
- Suitable for all dimmable OSRAM line voltage LED lamps

## Download Data

File
 Declarations of conformity Declaration of conformity DALI PRO CONT-4 DALI PRO PB Coupler DALI PRO Sen
 Installation/Operation notice HTi DALI 315 DIM Installation Guide
 CAD data 3-dim HTM 150
 CAD data 3-dim HTM 150

## Logistical Data

Product code	Product description	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Volume	Gross weight
4008321957344	HTI DALI 315 DIM	Shipping carton box 25	292 mm x 300 mm x 260 mm	22.78 dm <sup>3</sup>	4368.00 g

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

## Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.