

Logistic Data

| | |
|---------------------------|---------------------------|
| Article No. | 32418266 |
| Code | RCC-T 70W/WDL/230/G12 |
| Product EAN | 4008597182662 |
| Customs tariff no. | 85393290 |
| Box quantity (pcs.) | 12 |
| EAN Box | 4008597482663 |
| Gross weight of box in kg | 0.586 |
| Length of box in m | 0.18 |
| Width of box in m | 0.14 |
| Height of box in m | 0.16 |
| ETIM class | EC000037 |
| ETIM class name | Halogen metal halide lamp |
| Product status | Active |

Electric Parameters


| | |
|------------------------------|---------------|
| Lamp nominal wattage | 70 W |
| Rated wattage | 73.0 W |
| Energy Consumption kWh/1000h | 80,3 |
| Mains voltage | 230 V |
| Ignition voltage | 3.6 up to 5.0 |
| Lamp's nominal current | 1 A |
| Nominal current (A) | 0.96 A |
| Nominal choke current | 1 A |


Light Application Parameters

| | |
|---------------------------|--------------------|
| Luminous flux | 7400 lm |
| Luminous flux | 7400 lm |
| Luminous efficiency | 101.37 lm/W |
| Radium light colour | warm white de luxe |
| Colour temperature | 3000 K |
| Colour rendering index Ra | 89 |

Service Life

| | |
|-------------------|---------------|
| Mean service life | 15000/12000 h |
|-------------------|---------------|





Specification

| | |
|-------------|--------------------|
| Length max. | 100 mm |
| Lamp shape | Tube, single-ended |

Notes

Please, refer to www.radium.de/recycling for notes on disposal of burned-out lamps as well as lamp breakage.

The field 'info about service life' contains the frame conditions according to standards based on which the specific service life has been determined. So, for example, "12B50, 50Hz" means that the mean service life (B50) has been determined with a 12h switching cycle at mains (frequency 50Hz), "3B50, HF" is based on a 3h switching cycle at electronic control gear (high frequency).

Notes

Base



G12
IEC/EN 60061-1
sheet 7004-63-2

Spectrum

Natural daylight is a mixture of direct sunlight and the light of the sky. Therefore, its spectral composition changes permanently due to the changing time of day. The standardised light classification D65 corresponds to a daylight with a colour temperature of approximately 6500 K.


Every discharge lamp type has got an individual spectral power distribution according to its chemical filling. From this result important properties light colour or colour rendering.

Should the spectral lines be very close together the lamp presumably has got a very good colour rendering index, so, Ra might be near 100. Does the spectrum rather look like single lines or frayed out the colour rendering of the lamp will probably be not as good.


If number and height of the spectral lines within the blue range (around 400 nm) prevails it might be a lamp with a rather cold light colour like for example daylight. On the other hand, should the red (around 700 nm) or the red and yellow (around 600 nm) range be dominant one can assume that the lamp will be a rather warm light colour like WDL.

After the lamp start a metal halide lamp needs about 2-4 minutes time to reach its full luminous flux, all colours in the spectrum are within the discharge arc then.

Visible region from 380 to 780 nm; height of graph corresponding with relative spectral emission (400mW/klm) per 10nm.



RCC.../WDL



daylight(D 65)

Special features



General notes

The technical design data in accordance with DIN and IEC. The producer does not take any responsibility for damage to persons or property in case of unsuitable operation or handling of the product. Operating data and dimensions are valid within the usual tolerances. Related lamp types (different bases, mains voltages) may be available on request. Sale and delivery are effected in accordance with the Radium Terms of Delivery and Payment valid on the day of conclusion of contract. Packing units offer economical advantages to the purchase and logistic department. Please match your quantity volume accordingly. For orders of a minimum quantity (clefts) with a lamp model the amount lower than the volume of each packaging unit, we will invoice 10 % additional charge per lamp type. Technical changes and terms of delivery are reserved. Manipulation of any kind to packaging or product is not permissible as this will violate Radium brand rights. Furthermore, technical properties of the product can change to its disadvantage or even destruction. Therefore, Radium cannot be responsible for consequential damages.

@ = Registered trademark

Subject to change without notice. Errors and omissions excepted.

All technical data without guarantee.