

## Lynx TE

LYNX-TE 26W/840 FSD  
0027855



### Product features

- Triple bend compact pin-base lamps, - Suitable for operation on electronic ballasts, - Excellent luminous flux , - Excellent colour rendering, - Dimmable with suitable dimmer



## PRODUCT OVERVIEW

IPC Code	0027855
Product name	LYNX-TE 26W/840 FSD
Technology	Compact Fluorescent
Watt (Rated) (W)	26
Lamp shape	CFLni
Cap/Base	GX24q-3
Lamp finish	Frosted
Fixture rating	Open
General application	Education, Hospitality, Logistics & Industry, Museums & Galleries, Office, Retail, Residential & Consumer
Certifications	EUERL036
ETIM Class	EC000087
E-number FI	4944140
E-number SE	8357432
E-number Norway	3802805
Luminous flux (lm)	1800
Colour temperature (K)	4000
Light colour	Cool White
CRI (Ra)	82
Wattage (W)	26
Product Voltage (V)	220
Dimmable	No
Average life (Nominal) (h)	12000
Product EAN number	5410288278551

## DATA TABLE

### General data

IPC Code	0027855
Product name	LYNX-TE 26W/840 FSD
Technology	Compact Fluorescent
Watt (Rated) (W)	26
Lamp shape	CFLni
Cap/Base	GX24q-3

## Lynx TE

*LYNX-TE 26W/840 FSD*  
0027855

Lamp finish	Frosted
Fixture rating	Open
General application	Education, Hospitality, Logistics & Industry, Museums & Galleries, Office, Retail, Residential & Consumer
Certifications	EUERL036
ETIM Class	EC000087
E-number FI	4944140
E-number SE	8357432
E-number Norway	3802805

### Optical data

Luminous flux (lm)	1800
Luminous flux (Rated) (lm)	1800
Rated lamp efficacy 100h 50Hz at 25°C (lm/W)	66
Rated lamp efficacy 100h 50Hz at optimum temp. (lm/W)	66
Rated lamp efficacy 100h HF at 25°C (lm/W)	69.00
Ambient temperature for maximum luminous flux (°C)	25
Colour temperature (K)	4000
Light colour	Cool White
Colour Code	840
CRI (Ra)	82
Adjustable chromaticity	N
Rated lumen maint. factor (%) at 2000 h 50Hz	85
Rated lumen maint. factor (%) at 4000 h 50Hz	84
Rated lumen maint. factor (%) at 8000 h 50Hz	81
Rated lumen maint. factor (%) at 16000 h 50Hz	78
Rated lumen maint. factor (%) at 20000 h 50Hz	75

### Electrical data

Wattage (W)	26
Starting time (max) (s)	10 Sec
Current (A)	0.325
Product Voltage (V)	220
Control gear required	Yes
Transformer required	No
Dimmable	No
Lamp Energy Label (class)	A
Energy efficiency level	A
kWh per 1000 hours burning time	28

### Lifetime data

Average life (Nominal) (h)	12000
----------------------------	-------

## Lynx TE

*LYNX-TE 26W/840 FSD*  
0027855

Average life (Rated) (h)	12000
Rated survival factor (%) at 2000 h 50Hz	96
Rated survival factor (%) at 4000 h 50Hz	90
Rated survival factor (%) at 6000 h 50Hz	80
Rated survival factor (%) at 8000 h 50Hz	72
Rated survival factor (%) at 12000 h 50Hz	70
Rated survival factor (%) at 16000 h 50Hz	60
Rated survival factor (%) at 20000 h 50Hz	25

### Physical data

Max. Length base to base (mm) - A	141
Max. Lamp Diameter (mm) - D	49
Weight (kg)	0.069


### Packaging

Single packaging type	Carton
Product EAN number	5410288278551
Packaging single length / height (cm)	4.8
Packaging single width (cm)	4.8
Packaging single depth (cm)	13.6
DUN14 (outer)	15410288278558
Units per outer package	10
Packaging outer length / height (cm)	26.4
Packaging outer width (cm)	10.8
Packaging outer depth (cm)	14.2

### Safety data

Lamp mercury content (mg)	2.5
Breakage cleaning instructions	Applicable
Recommendation for disposal at end of life	Applicable
Special purpose lamp	No
Intended purpose	General lighting
Dry applications use only	Yes
Suitable for household illumination	Yes

## TECHNICAL DRAWINGS



Lynx TE  
LYNX-TE 26W/840 FSD  
0027855

