Q-MAX UV disinfection luminaire DIRECT I



1x36W incl. tube

UV disinfection luminaire DIRECT 1x30W

Technical details:

- Area: up to 15m2
- Power supply: 220-240V 50/60Hz
- Power: 32W
- Service life: 9000 Std.
- UVC on HF ballast: at least 13,1 W
- Weight: 5 kg
- Necessary replacement of the UV-C lamp: 1 per year
- Installation: wall, ceiling, stand
- Contains 1 Philips lamp (254nm UVC)
- Width: 165mm
- Length: 940mm
- Depth without suspension: 80mm / with: 135mm
- Disinfection time: >15 min

Product No.: 33589

UV disinfection luminaire DIRECT 1x36W

Technical details:

- Area: up to 17m2
- Power supply: 220-240V 50/60Hz
- Power: 38W
- Service life: 9000 Std.
- UVC on HF ballast: at least 15,5 W
- Weight: 6 kg
- Necessary replacement of the UV-C lamp: 1 per year
- Installation: wall, ceiling, stand
- Contains 1 Philips lamp (254nm UVC)
- Width: 165mm
- Length: 1240mm
- Depth without suspension: 80mm / with: 135mm
- Disinfection time: >15 min

Product No.: 33591

Intended use:

Air and surface disinfection, prevention of secondary infections. Kills bacteria, viruses, fungi and mould...

Fields of application:

Production halls, hospitals, medical facilities, pharmacies, public transport and many more.



UV disinfection luminaire **DIRECT II**

Q-MAX



2x36W incl. tubes

UV disinfection luminaire DIRECT 2x30W

Technical details:

- Area: up to 25m2
- Power supply: 220-240V 50/60Hz
- Power: 64W
- Service life: 9000 Std.
- UVC on HF ballast: at least 26,2 W
- Weight: 5,3 kg
- Necessary replacement of the UV-C lamp: 1 per year
- Installation: wall, ceiling, stand
- Contains 2 Philips lamps (254nm UVC)
- Width: 245mm
- Length: 940mm
- Depth without suspension: 80mm / with: 135mm
- Disinfection time: >15 min

Product No.: 33590

UV disinfection luminaire DIRECT 2x36W

Technical details:

- Area: up to 27m2
- Power supply: 220-240V 50/60Hz
- Power: 74W
- Service life: 9000 Std.
- UVC on HF ballast: at least 31 W
- Weight: 6,3 kg
- Necessary replacement of the UV-C lamp: 1 per year
- Installation: wall, ceiling, stand
- Contains 2 Philips lamps (254nm UVC)
- Width: 245mm
- Length: 1240mm
- Depth without suspension: 80mm / with: 135mm
- Disinfection time: >15 min

Product No.: 33592

Intended use:

Air and surface disinfection, prevention of secondary infections. Kills bacteria, viruses, fungi and mould...

Fields of application:

Production halls, hospitals, medical facilities, pharmacies, public transport and many more.



Special combination of indirect air disinfection and direct air and surface disinfection. The hybrid enables continuous 24-hour disinfection of the air and direct disinfection as soon as there is nobody left in the room.

Choose the hybrid version for maximum flexibility and protection. To ensure maximum safety, the indirect mode is controlled separately from the direct mode.

UV disinfection luminaire HYBRID 3x30W

Technical data:

- Area: up to 25m2 indirect / 15m2 direct
- Power supply: 220-240V 50/60Hz
- Power: 70W
- Lifetime: 9000 hours
- Fan capacity: 125 m3/hour
- Recommended operating time: indirect 24 hours >/ 15 min direct
- UVC on HF ballast: minimum 39.9 W
- Weiaht: 11 ka
- Necessary replacement of the UV-C lamps: 1x per year
- Replacement of the air filter: Depending on use (2x per year rec.)
- Installation: wall, ceiling, stand
- Contains 3 Philips lamps (254nm UVC)
- Width: 245mm / Length: 1300mm / Depth: 180mm
- Preduct No.: 33618

Intended use & Application areas:

Air and surface disinfection, prevention of secondary infections. Kills bacteria, viruses, fungi and mould. Production halls, hospitals, medical facilities, pharmacies, public transport and many more.

UV disinfection luminaire HYBRID 3x36W

Technical data:

- Area: up to 25m2 indirect / 17m2 direct
- Power supply: 220-240V 50/60Hz
- Power: 138W
- Lifetime: 9000 hours
- Fan capacity: 125 m3/hour
- Recommended operating time: indirect 24 hours >/ 15 min direct
- UVC on HF ballast: at least 46.5 W
- Weiaht: 13 ka
- Necessary replacement of the UV-C lamps: 1x per year
- Replacement of the air filter: Depending on use (2x per year rec.)
- Installation: wall, ceiling, stand
- Contains 3 Philips lamps (254nm UVC)
- Width: 245mm / Length: 1300mm / Depth: 180mm

Product No.: 33619

UV disinfection luminaire TUBE 2x30W

Technical data:


- Area: up to 35m2
- Power supply: 220-240V 50/60Hz
- Power: 88W
- Lifetime: 9000 hours
- Fan capacity: 117 m3/h
- Recommended operating time: 24 hours
- UVC power: 26.2 W minimum
- UVC on HF device: min. 40 W (in chamber flow)
- Weight: 9 kg
- Necessary replacement of the UV-C lamps: 1 per year
- Replacement of the air filter: Depending on use (2x per year rec.)
- Installation: wall, ceiling, stand
- Contains 2 Philips lamps (254nm UVC)
- Width: 250mm / Length: 1300mm / Depth with suspension: 305mm

Product No.: 33616

Intended use & Application areas:

Air disinfection, prevention of secondary infections. Kills bacteria, viruses, fungi and mould. Production halls, hospitals, medical facilities, pharmacies, public transport and many more.

Protective foil, wireless control, remote control, tripod, mounting arm, motion sensor





UV disinfection luminaire TUBE 2x36W

Technical data:

- Area: up to 35m2
- Power supply: 220-240V 50/60Hz
- Power: 100W
- Lifetime: 9000 hours
- Fan capacity: 117 m3/h
- Recommended operating time: 24 hours
- UVC power: at least 31 W
- UVC on HF device: min. 40 W (in chamber flow)
- Weight: 11 kg
- Necessary replacement of the UV-C lamps: 1 per year
- Replacement of the air filter: Depending on use (2x per year rec.)
- Installation: wall, ceiling, stand
- Contains 2 Philips lamps (254nm UVC)
- Width: 250mm / Lenath: 1300mm / Depth with suspension: 305mm

Product No.: 33617





UV disinfection luminaire **DIRECT 600**

UV disinfection luminaire INDIRECT 600

Q-MAX



UV disinfection luminaire DIRECT 600

Technische Daten:

- Area: up to 22m2
- Power supply: 220-240V 50/60Hz
- Power: 82W
- Lifetime: 9000 hours
- UVC on HF ballast: minimum 24 W
- Weiaht: 5 ka
- Necessary replacement of the UV-C lamps: 1 per vear
- Installation: Ceiling
- Contains 4 Philips lamps (254nm UVC)
- Width & Length: 595mm
- Depth: 75mm
- Ceiling cut-out: 580 x 580mm
- Disinfection time: >15 min Product No.: 33620

Intended use:

Air and surface disinfection, prevention of secondary infections. Kills bacteria, viruses, fungi and mould.

Fields of application:

Production halls, hospitals, medical facilities, pharmacies, public transport and many more.

UV disinfection luminaire INDIRECT 600

Technische Daten:

- Area: up to 22m2
- Power supply: 220-240V 50/60Hz
- Power: 100W
- Lifetime: 9000 hours
- UVC on HF ballast: minimum 24 W
- Weiaht: 9 ka
- Necessary replacement of the UV-C lamps: 1 per
- vear
- Installation: Ceiling
- Contains 4 Philips lamps (254nm UVC)
- Width & Length: 595mm
- Depth: 75mm
- Ceiling cut-out: 580 x 580mm
- Disinfection time: >15 min Product No.: 33621

Intended use:

Air disinfection, prevention of secondary infections. Kills bacteria, viruses, fungi and mould.

Fields of application:

Production halls, hospitals, medical facilities, pharmacies, public transport and many more



