



MSD Platinum – The power to light your creativity

MSD Platinum (Touring/Stage)

The MSD Platinum lamps open up new levels of creative freedom in entertainment lighting, with powerful, compact and brilliantly intense light. Their compact, lightweight design provides the freedom to create smaller, lighter luminaires – for use at any location on stage. And their short arc, high color temperature and innovative reflector produce a sparkling, high beam intensity for outstanding color reproduction. They also offer long and reliable lifetime, high efficacy and fast replacement times. It all adds up to an intensely exciting creative experience.

Vorteile

- High beam intensity
- Freedom to create smaller and lighter fixtures
- High perceived brightness
- A long and reliable performance

Merkmale

- Very short arc
- Compact system
- High correlated color temperature
- Philips Platinum technology

Anwendung




- Events
- Shows/Theater
- Tournée/Bühne

MSD Platinum (Touring/Stage)

Versions



Abmessungsskizzen



Product	D (max)	O	C (max)
MSD Platinum 21 R 1CT/8	54 mm	1.2 mm	60 mm
MSD Platinum 20 R 1CT/8	58.5 mm	1.2 mm	72 mm

Product	D (max)	O	C (max)
MSD Platinum 16 R 1CT/8	58.5 mm	1.3 mm	66.4 mm
MSD Platinum 15 R 1CT/8	58.5 mm	1.3 mm	66.4 mm

Product	D (max)	T (max)	O	C (max)
MSD Platinum 5 R 1CT/8	51.4 mm	6.8 mm	1.0 mm	57.1 mm
MSD Platinum 14 R 1CT/8	51.5 mm	6.8 mm	0.95 mm	57.1 mm

MSD Platinum (Touring/Stage)

Dimmen	
Dimmbar	Ja
Allgemeine Eigenschaften	
Sockel	-
Hauptanwendungsgebiet	Stage/Touring
Betriebsstellung	UNIVERSAL
Lichttechnische Daten	
Farbcode	2
Farbwiedergabeindex (nom.)	-

Elektrische Kenndaten

Order Code	Full Product Name	Spannung (max.)	Spannung (min.)	Nennleistung (nom.)
93070200	MSD Platinum 5 R 1CT/8	-	-	189 W
44061200	MSD Platinum 14 R 1CT/8	-	-	280 W
13535700	MSD Platinum 15 R 1CT/8	-	-	300 W

Order Code	Full Product Name	Spannung (max.)	Spannung (min.)	Nennleistung (nom.)
70438600	MSD Platinum 16 R 1CT/8	-	-	330 W
47812700	MSD Platinum 20 R 1CT/8	110 V	85 V	470 W
67826800	MSD Platinum 21 R 1CT/8	-	-	470 W

Allgemeine Eigenschaften

Order Code	Full Product Name	Lebensdauer bis 50 % Ausfall (nom.)	Systembeschreibung
93070200	MSD Platinum 5 R 1CT/8	3000 h	Reflector-E20.6
44061200	MSD Platinum 14 R 1CT/8	2000 h	Reflector-E20.6
13535700	MSD Platinum 15 R 1CT/8	2000 h	na

Order Code	Full Product Name	Lebensdauer bis 50 % Ausfall (nom.)	Systembeschreibung
70438600	MSD Platinum 16 R 1CT/8	1500 h	Reflector E21.9 TCM
47812700	MSD Platinum 20 R 1CT/8	1500 h	Reflector E21.9 TCM
67826800	MSD Platinum 21 R 1CT/8	1500 h	-

Lichttechnische Daten

Order Code	Full Product Name	Ähnlichste Farbtemperatur (nom.)	Lichtstrom (min.)	Lichtstrom (nom.)
93070200	MSD Platinum 5 R 1CT/8	8000 K	7100 lm	7950 lm
44061200	MSD Platinum 14 R 1CT/8	7800 K	-	12350 lm
13535700	MSD Platinum 15 R 1CT/8	8000 K	11000 lm	13500 lm

Order Code	Full Product Name	Ähnlichste Farbtemperatur (nom.)	Lichtstrom (min.)	Lichtstrom (nom.)
70438600	MSD Platinum 16 R 1CT/8	8000 K	14300 lm	16000 lm
47812700	MSD Platinum 20 R 1CT/8	8000 K	-	22400 lm
67826800	MSD Platinum 21 R 1CT/8	8000 K	14100 lm	15600 lm

