



Halogen reflector

13938XHP 50W GX5.3 22.8V 1CT/24

Philips' halogen reflector lamps offer the ideal no-fuss solution for a wide variety of medical, projection and scientific illumination systems. Their proven reliability makes them ideal for retrofit installations. The burners are precisely aligned for optimal light performance. Dichroic reflectors ensure heat dissipation towards the back of the optical system, which helps the optical system remain within temperature limits. A special blue-filter version blocking out unwanted light above 700 nm is available for dental curing applications. In addition, you get all the proven advantages of halogen technology such as a CRI of 100 – the same as natural sunlight for the best possible color rendering. Halogen lamps also create a comfortable warm white light, and they maintain their high lumen output with almost no lumen reduction throughout their lifetime.

Product data


General Information		Voltage (Nom)	
Cap-Base	GX5.3 [GX5.3]	22.8 V	
Philips Code	13938XHP	Controls and Dimming	
ANSI Code	-	Dimmable	Yes
LIF Code	-	Mechanical and Housing	
Operating Position	UNIVERSAL [Any or Universal (U)]	Bulb Material	Quartz-UV Open
Main Application	Projection	Reflector Finish	Smooth
Life to 50% Failures (Nom)	750 h	Filament Dimensions WxH	-
Light Technical		Luminaire Design Requirements	
Luminous Flux (Rated) (Nom)	380 lm	Bulb Temperature (Max)	900 °C
Correlated Color Temperature (Nom)	3200 K	Pinch Temperature (Max)	350 °C
Color Rendering Index (Nom)	100	Product Data	
Operating and Electrical		Full product code	871869669019200
Power (Rated) (Nom)	50 W		

Halogen reflector

Order product name	13938XHP 50W GX5.3 22.8V 1CT/24
EAN/UPC - Product	8718696690192
Order code	924059828302
Numerator - Quantity Per Pack	1
Numerator - Packs per outer box	24

Material Nr. (12NC)	924059828302
Net Weight (Piece)	27.000 g

Dimensional drawing



13938XHP 50W GX5.3 22.8V

Product	D (max)	C (max)
13938XHP 50W GX5.3 22.8V 1CT/24	50 mm	45 mm

