


PRODUCT REQUIREMENT SHEET

See LV 75-32

MEASURING VOLTAGE	400V (stabilisation 3 min.)
MEASURING POSITION	Horizontal
LIFE TEST POSITION	Horizontal Free air burning
BURNING POSITION	P15
SWITCHING CYCLE	Continuous
AGEING	1h at rated voltage

	VALUE UNIT	TOLERANCE
WATTAGE	2500W	± 6 %
LIFE	5000 h	average
COLOR TEMPERATURE Clear lamp Lamp with reflector	2700 K 2600 K	± 100 K Indicative value
FLUX (HeLeN lamp) Clear lamp Reduction	NA NA	
WEIGHT	45 g	

1 0833	2 0833	3 0000	4	5	6	7	8	
SUPERSEDES : 9245 561 49100 0833/000 p. 190-2 Of 08/07/2011		HALOGEN LAMP INFRARED INDUSTRIAL REFLECTOR 14143Z/98 2500W 400V REFL			9245 561 49100 0833/000		14/01/2013	
REF. : PDM IRK 2012-060	DOCUMENTATION	UNIT mm	PROJ EUROP 	2 SH	SH	190-2	10	A4
NOM : J.P. CHARLIER	VALIDATION : A. PICHARD			DR. FISCHER Europe				
All rights reserved. Reproduction in whole or in part is prohibited without the written consent of the copyright owner.								