



Halogen reflector

6423FO 150W GZ6.35 15V 1CT/10X5F

Philips' halogen reflector lamps offer the ideal no-fuss solution for a wide variety of medical, projection and scientific illumination systems. Their proven reliability makes them ideal for retrofit installations. The burners are precisely aligned for optimal light performance. Dichroic reflectors ensure heat dissipation towards the back of the optical system, which helps the optical system remain within temperature limits. A special blue-filter version blocking out unwanted light above 700 nm is available for dental curing applications. In addition, you get all the proven advantages of halogen technology such as a CRI of 100 – the same as natural sunlight for the best possible color rendering. Halogen lamps also create a comfortable warm white light, and they maintain their high lumen output with almost no lumen reduction throughout their lifetime.

Product data

General Information		
Cap-Base	GZ6.35 [GZ6.35]	
Philips Code	6423FO	
ANSI Code	EFR	
LIF Code	A1/232	
Operating Position	P90/P15	
Main Application	Projection	
Life to 50% Failures (Nom)	50 h	
J Code	-	
Light Technical		
Luminous Flux (Nom)	840 lm	
Correlated Color Temperature (Nom)	3380 K	
Color Rendering Index (Nom)	100	

Operating and Electrical	
Power (Rated) (Nom)	150 W
Voltage (Nom)	15 V
Controls and Dimming	
Dimmable	Yes
Mechanical and Housing	
Cap-Base Information	-
Bulb Material	Quartz-UV Open
Reflector Finish	-
Filament Shape	-
Filament Dimensions WxH	-
Luminaire Design Requirements	
Bulb Temperature (Max)	900 °C


Datasheet, 2017, November 13 data subject to change

Halogen reflector

Pinch Temperature (Max)	400 °C		
Working Distance WD	32 mm		
Product Data			
Full product code	871150040971360		
Order product name	6423FO 150W GZ6.35 15V 1CT/10X5F		
EAN/UPC - Product	8711500409713		

Order code	924048218504
Numerator - Quantity Per Pack	1
Numerator - Packs per outer box	50
Material Nr. (12NC)	924048218504
Net Weight (Piece)	0.024 kg

Dimensional drawing



Product	D (max)	C (max)
6423FO 150W GZ6.35 15V 1CT/10X5F	50 mm	42 mm

