

HBO 200 W/DC 57 V

HBO | Mercury short-arc lamps without reflector 50...200 W



Areas of application


- Fluorescence microscopy
- UV curing
- A variety of light guide applications

Product benefits

- High radiance
- High radiant power in the UV and the visible range

Product features

- Multi-line spectrum



Product datasheet

Technical data

Electrical data

Nominal wattage	200.00 W
Lamp wattage	200 W
Nominal voltage	57.0 V
Lamp voltage	48...65 V ¹⁾
Lamp current	3.0...4.3 A
Type of current	DC



¹⁾ Initial electrical values

Photometrical data

Nominal luminous flux	10000 lm
Luminous intensity	1100 cd ¹⁾

¹⁾ Typical initial photometric value

Dimensions & weight



Diameter	17.0 mm
Mounting length	102.0 mm ¹⁾
Length with base excl. base pins/connection	102.00 mm ¹⁾
Light center length (LCL)	40.0 mm ²⁾

¹⁾ Maximum

²⁾ Distance from end of base to tip of anode (cold)

Lifespan

Lifespan	1000 h
----------	--------

Additional product data

Base (standard designation)	SFc10-4/15
Base anode (standard designation)	SFc10-4

Product datasheet

Base cathode (standard designation)	SFc10-4
--	---------

Capabilities

Burning position	s90 ¹⁾
-------------------------	-------------------

¹⁾ Anode underneath

Country specific information

Product code	METEL code	SEG-No.	STK-Number	UK Org
4050300506791	OSRHBO200DC	-	-	-

Product datasheet

Safety advice

Because of their high luminance, UV radiation and high internal pressure (when hot) HBO lamps may only be operated in enclosed lamp casings specially constructed for the purpose. Mercury is released if the lamp breaks. Special safety precautions must be taken. More information is available on request or can be found in the leaflet included with the lamp or in the operating instructions.

Logistical Data

Product code	Product description	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Volume	Gross weight
4050300506791	HBO 200 W/DC 57 V	Folding carton box 1	165 mm x 48 mm x 95 mm	0.75 dm ³	113.00 g
4050300506807	HBO 200 W/DC 57 V	Shipping carton box 10	235 mm x 210 mm x 225 mm	11.10 dm ³	1358.00 g

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

References / Links

Further technical information on HBO lamps and information for manufacturers of operating equipment can be requested directly from OSRAM.

Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.
